

PRODUCT FICHE HOOD

Trademark	INDESIT
Model identifier	ISLK 66 LS X
Annual Energy Consumption	65,5 kWh/a
Energy Efficiency Class	D
Fluid Dynamic Efficiency	8,1
Fluid Dynamic Efficiency class	E
Lighting efficiency in lux/Watt	13,0 lux/W
Lighting efficiency class	D
Grease filtering efficiency	66,0 %
Grease filtering efficiency class	D
Minimum air flow	115 m ³ /h
Maximum Air flow	272 m ³ /h
Air flow boost	0 m ³ /h
A-weighted sound power at min. speed	52 dB(A)
A-weighted sound power at max. speed	71 dB(A)
A-weighted sound power boost	0 dB(A)
Power consumption in off-mode	0,00 W
Power consumption in standby mode	0,00 W
Time increase factor (f)	1,7
Energy Efficiency Index (EEI_{hood})	90,0
Measured air flow rate at best efficiency point (Q_{BEP})	160,0 m ³ /h
Measured air pressure at best efficiency point (P_{BEP})	180 Pa
Measured electric power input at best efficiency point (W_{BEP})	98,5 W
Nominal power of the lighting system (W_L)	6,0 W
Average illumination of the lighting system on the cooking surface (E_{middle})	78 lux