

**IGW 324 IX** 

12NC/Fx: F102923

## GTIN (EAN) code: 8050147029237

| DIMENSION  | <b>MEAS</b> | UR              |
|--|-------------|-----------------|
| OVERALL CABINET  |             |                 |
| MIN Height of the wall cabinet niche, including all required space for installation or ventilation | 0           | mm              |
| MIN Height of the tall cabinet niche, including all required space for installation or ventilation | 583         | mm              |
| MIN Height of the base cabinet niche, including all required space for installation or ventilation | 600         | mm              |
| MAX Height of the wall cabinet niche, including all required space for installation or ventilation | 0           | mm              |
| MAX Height of the tall cabinet niche, including all required space for installation or ventilation | 585         | mm              |
| MAX Height of the base cabinet niche, including all required space for installation or ventilation | 601         | mm              |
| MIN Width of the wall cabinet niche, including all required space for installation or ventilation  | 0           | mm              |
| MIN Width of the tall cabinet niche, including all required space for installation or ventilation  | 560         | mm              |
| MIN Width of the base cabinet niche, including all required space for installation or ventilation  | 560         | mm              |
| MAX Width of the wall cabinet niche, including all required space for installation or ventilation  | 0           | mm              |
| MAX Width of the tall cabinet niche, including all required space for installation or ventilation  | 568         | mm              |
| MAX Width of the base cabinet niche, including all required space for installation or ventilation  | 568         | mm              |
| MIN Depth of the wall cabinet niche, including all required space for installation or ventilation  | 0           | mm              |
| MIN Depth of the tall cabinet niche, including all required space for installation or ventilation  | 560         | mm              |
| MIN Depth of the base cabinet niche, including all required space for installation or ventilation  | 560         | mm              |
| Space in front, which is required to install bottom trim   | 9           | mm              |
| Indicates whether a ventilation opening is needed or not. Default is "N"                           | Yes         |                 |
| WALL CABINET (vent-shaft incoming)   |             |                 |
| Indicates the position of the freespace for the inbound airflow (wall cabinet)                     | Rear        |                 |
| Minimum space or inbound ventilation (wall cabinet)  | 0           | mm              |
| Minimum area for inbound ventilation cavity (wall cabinet)   | 0           | cm <sup>2</sup> |
| WALL CABINET (vent-shaft outgoing)   |             |                 |
| Indicates the position of the freespace for the outbound airflow (wall cabinet)                    | Rear        |                 |
| Minimum space or outbound ventilation (wall cabinet)   | 0           | mm              |
| Minimum area for outbound ventilation cavity (wall cabinet)  | 0           | cm <sup>2</sup> |
| TALL CABINET (vent-shaft incoming)   |             |                 |
| Indicates the position of the freespace for the inbound airflow (tall cabinet)                     | Rear        |                 |
| Minimum space for inbound ventilation (tall cabinet)   | 45          | mm              |
| Minimum area for inbound ventilation cavity (tall cabinet)   | 150         | cm <sup>2</sup> |
| TALL CABINET (vent-shaft outgoing)   |             |                 |
| Indicates the position of the freespace for the outbound airflow (tall cabinet)                    | Rear        |                 |
| Minimum space for outbound ventilation (tall cabinet)  | 0           | mm              |
| Minimum area for outbound ventilation cavity (tall cabinet)  | 150         | cm <sup>2</sup> |
| BASE CABINET (vent-shaft incoming)   |             |                 |
| Indicates the position of the freespace for the inbound airflow (base cabinet)                     | Rear        |                 |
| Minimum space for inbound ventilation (base cabinet)   | 45          | mm              |
| Minimum area for inbound ventilation cavity (base cabinet)   | 150         | cm <sup>2</sup> |
| BASE CABINET (vent-shaft outgoing)   |             |                 |
| Indicates the position of the freespace for the outbound airflow (base cabinet)                    | Rear        |                 |
| Minimum space for outbound ventilation (base cabinet)  | 0           | mm              |
| Minimum area for outbound ventilation cavity (base cabinet)  | 150         | cm <sup>2</sup> |

| DIMENSION MEA   |     | ASURE |  |
|---|-----|-------|--|
| APPLIANCE   |     |       |  |
| Height of the front   | 595 | mm    |  |
| Width of the front  | 595 | mm    |  |
| Depth of the front  | 20  | mm    |  |
| Maximum depth all protruding elements, e.g. handles, controls   | 47  | mm    |  |
| Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees    | 3   | mm    |  |
| Projection of front in relation to housing of appliance   | 20  | mm    |  |
| Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable | 5   | mm    |  |
| When product panel is missing, set to 0   | 97  | mm    |  |
| Space in front, which is required to guarantee full operability. The most protruding part gives this dimension                  | 460 | mm    |  |
| Height from bearing area of appliances and lower handle   | 450 | mm    |  |
| Frontal handle thickness  | 30  | mm    |  |
| Frontal handle width  | 590 | mm    |  |
| MIN Height of the product body  | 570 | mm    |  |
| MAX Height of the product body  | 570 | mm    |  |
| Width of the product body   | 558 | mm    |  |
| Depth of the product body   | 548 | mm    |  |
| Full depth of product excluding protruding interface elements   | 570 | mm    |  |
| Appliance can be used as base for other appliances from the same manufacturer. Default is "No"                                  | No  |       |  |
| Appliance Flap door   |     |       |  |
| Projection of the opened flap in relation to bearing area   | 0   | mm    |  |
| Maximum angle when flap door is opened totally  | 89  | mm    |  |
| Appliance Side swing door   |     |       |  |
| Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted                   | 0   | mm    |  |
| Lateral projection of opened front at the side where the hinge is fixed   | 0   | mm    |  |
| Maximum angle when door is opened totally   | 0   | mm    |  |
| Appliance other   |     |       |  |
| Depth from front end of the niche to the front end of the freespace of the retrace  | 428 | mm    |  |
| Height from niche to bottom end of freespace for the retrace  | 525 | mm    |  |