| PRODUCT FICHE HOOD  |              |
|---|--------------|
| Trademark   | WHIRLPOOL    |
| Model identifier  | AKR 559/2 IX |
| Annual Energy Consumption   | 123,0 kWh/a  |
| Energy Efficiency Class   | Е            |
| Fluid Dynamic Efficiency  | 5,1          |
| Fluid Dynamic Efficiency class  | F            |
| Lighting efficiency in lux/Watt   | 3,0 lux/W    |
| Lighting efficiency class   | G            |
| Grease filtering efficiency   | 76,0 %       |
| Grease filtering efficiency class   | С            |
| Minimum air flow  | 185 m³/h     |
| Maximum Air flow  | 368 m³/h     |
| Air flow boost  | 0 m³/h       |
| A-weighted sound power at min. speed  | 44 dB(A)     |
| A-weighted sound power at max. speed  | 61 dB(A)     |
| A-weighted sound power boost  | 0 dB(A)      |
| Power consumption in off-mode   | 0,00 W       |
| Power consumption in standby mode   | 0,00 W       |
| Time increase factor (f)  | 1,8          |
| Energy Efficiency Index (EEI <sub>hood</sub> )  | 107,0        |
| Measured air flow rate at best efficiency point (QBEP)                                    | 240,0 m³/h   |
| Measured air pressure at best efficiency point (PBEP)                                     | 95 Pa        |
| Measured electric power input at best efficiency point (W <sub>BEP</sub> )                | 125,0 W      |
| Nominal power of the lighting system (W <sub>L</sub> )                                    | 56,0 W       |
| Average illumination of the lighting system on the cooking surface (E <sub>middle</sub> ) | 168 lux      |