
WHVS 93F LT BSS/1

12NC: 859991652070

GTIN (EAN) code: 8003437636684







- Maximum noise level 67 dBA
- Air Flow (min. max.): 130, 640, booster 770 m3/h
- Maximum extraction rate: 640 (m3/h)
- Energy class B
- Extraction / Recirculation Rate %Z_REQ_MAX_OUT_EXTRACTION% / 430 m3/h
- 3 speed settings
- ZenMode
- 2 LED, 5 W lamps
- 1 x 250 W motor
- Perimetral aspiration
- **Electronic Touch control**
- 2 Washable aluminium filters
- Grease Filtering Efficiency Class: E
- Lighting Efficiency Class: A
- Fluid Dynamic Efficiency Class: B
- Operating Mode: Air extraction, Recirculating air

Whirlpool wall mounted cooker hood - WHVS 93F LT BSS/1

This Whirlpool wall mounted Cooker Hood features: black color. Dishwasher-safe, washable aluminium grease filters. LED lights for ideal lighting. An outstanding cooker extractor fan, ensuring a fresh, grease-free cooking environment. High-efficiency S40HE motor.



LED lighting

Increased energy and cost efficiency. The LED lighting system lasts 10 times longer than traditional bulbs and uses 90% less energy.



ZenMode

Providing the ideal balance between performance and silence, Whirlpool's ZenMode ensures the hood is powerful enough to keep the air fresh and clean while making the kitchen a quieter, more enjoyable place for cooking and socialising.



Electronic control

Effortless control. This Whirlpool Hood includes an intuitive electronic user interface, designed to provide you with the simplest, most satisfying user experience ever.



3 Speeds

Versatile performance. This Whirlpool Hood offers 3 speed options, giving you complete control over the extraction rate.



Wall-mounted installation

Wall-mounted installation. This wall-mounted Whirlpool Hood is a breeze to install.



Total annual energy consumption

Ideal performance, outstanding savings. Whirlpool Hoods are designed to provide exceptional results, while reducing energy costs.



High efficency motor

Efficiency first. The motor in this Whirlpool Hood is designed to provide ideal filtration, while ensuring high energy efficiency.



Carbon Filter Included

Enjoy fresh air in your kitchen, always. This Whirlpool Hood includes a carbon purifying air filter, that effectively protects your kitchen from odours and grease.



Flexible Installation

Flexible installation options. This Whirlpool Hood can be operated in either Ducted or Recirculated mode (filter needed), so you can enjoy complete freedom when designing your kitchen.

WHVS 93F LT BSS/1

12NC: 859991652070



GTIN (EAN) code: 8003437636684		

Product group Hood Colour body Black Material body Metal / glass Colour chimney Black Material chimney Stainless steel Typology Wall-mounted Installation type Wall-mounted Type of control settings - Decor panel options N/A Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 250-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 50/60 Plug type Schuko Chimney height (mm) 0 Height of product, without chimney (mm) 0 Height of the product 895 Width of the product 895 Depth of the product 6 Minimum niche height 0 Minimum niche height 0 Minimum niche width 0 Niche depth 0 </th <th colspan="3">MAIN FEATURES</th>	MAIN FEATURES		
Material body Metal / glass Colour chimney Black Material chimney Stainless steel Typology Wall-mounted Installation type Wall-mounted Type of control Electronic Type of control settings - Decor panel options N/A Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) 0 Height of product, without chimney (mm) 0 Height of the product 895 Depth of the product 365 Width of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Product group	Hood	
Colour chimney Black Material chimney Stainless steel Typology Wall-mounted Installation type Wall-mounted Type of control Electronic Type of control settings - Decor panel options N/A Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 20-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 895 Depth of the product 365 Milimimum niche height 0 Milimimum niche width 0 Niche depth 0	Colour body	Black	
Material chimney Stainless steel Typology Wall-mounted Installation type Wall-mounted Type of control Electronic Type of control settings . Decor panel options N/A Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 20-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) 0 Height of product, without chimney (mm) 0 Height of the product 895 Depth of the product 895 Depth of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Material body	Metal / glass	
Typology Wall-mounted Installation type Wall-mounted Type of control Electronic Type of control settings - Decor panel options N/A Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) 0 Height of product, without chimney (mm) 0 Height of the product 895 Depth of the product 365 Minimum niche height 0 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Colour chimney	Black	
Installation type Installation	Material chimney	Stainless steel	
Type of control Electronic Type of control settings - Decor panel options N/A Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) 0 Height of product, without chimney (mm) 0 Height of the product 895 Depth of the product 365 Minimum niche height 0 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Туроlоду	Wall-mounted	
Type of control settings - Decor panel options N/A Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 895 Width of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Installation type	Wall-mounted	
Decor panel optionsN/AMotor locationIntegrated motor in hood bodyOperating ModeConvertibleElectrical connection rating (W)255Current (A)1,1Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)150Plug typeSchukoChimney height (mm)-Height of product, without chimney (mm)0Height of the product1475Width of the product895Depth of the product365Minimum niche height0Minimum niche width0Niche depth0	Type of control	Electronic	
Motor location Integrated motor in hood body Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 50/60 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 895 Width of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Type of control settings	-	
Operating Mode Convertible Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 895 Width of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Decor panel options	N/A	
Electrical connection rating (W) 255 Current (A) 1,1 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 895 Width of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Motor location	Integrated motor in hood body	
Current (A) 1,1 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) 0 0 Height of product, without chimney (mm) 0 1475 Width of the product 1475 Width of the product 1585 Depth of the product 1585 Minimum niche height 0 0 Niche depth	Operating Mode	Convertible	
Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)150Plug typeSchukoChimney height (mm)-Height of product, without chimney (mm)0Height of the product1475Width of the product895Depth of the product365Minimum niche height0Minimum niche width0Niche depth0	Electrical connection rating (W)	255	
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type Schuko Chimney height (mm) - Height of product, without chimney (mm) 0 Height of the product 1475 Width of the product 1895 Depth of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Niche depth 0	Current (A)	1,1	
Length of Electrical Supply Cord (cm) Plug type Schuko Chimney height (mm) Height of product, without chimney (mm) Height of the product Width of the product Width of the product Sept of the product	Voltage (V)	220-240	
Plug typeSchukoChimney height (mm)-Height of product, without chimney (mm)0Height of the product1475Width of the product895Depth of the product365Minimum niche height0Minimum niche width0Niche depth0	Frequency (Hz)	50/60	
Chimney height (mm) Height of product, without chimney (mm) Height of the product Width of the product Sept of the product Depth of the product Minimum niche height Minimum niche width Niche depth O Chimney height (mm) B 0 Chimney height (m	Length of Electrical Supply Cord (cm)	150	
Height of product, without chimney (mm) Height of the product Width of the product Depth of the product Minimum niche height Minimum niche width Niche depth O O O O O O O O O O O O O	Plug type	Schuko	
Height of the product 1475 Width of the product 895 Depth of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Chimney height (mm)	-	
Width of the product 895 Depth of the product 365 Minimum niche height 0 Minimum niche width 0 Niche depth 0	Height of product, without chimney (mm)	0	
Depth of the product365Minimum niche height0Minimum niche width0Niche depth0	Height of the product	1475	
Minimum niche height 0 Minimum niche width 0 Niche depth 0	Width of the product	895	
Minimum niche width 0 Niche depth 0	Depth of the product	365	
Niche depth 0	Minimum niche height	0	
	Minimum niche width	0	
Net weight (kg) 22	Niche depth	0	
	Net weight (kg)	22	

TECHNICAL FEATURE	S S
Type of manual control devices	Touch control
Type of automatic control devices	-
Number of motors	1
Total power of the motors (W)	250
Number of speed settings: boost option availability	3
Boost presence	No
Maximum output air extraction (m³/h)	640
Boost position air extraction (m³/h)	770
Maximum output recirculating air (m³/h)	430
Boost position output recirculating (m³/h)	450
Light Control Type	On/Off
Number of lights	2
Type of lamps used	LED
Total power of the lamps (W)	5
Diameter of air outlet (mm)	150
No-return airflow flap	Yes
Grease filter material	Washable aluminium
Odour filter	Yes

PERFORMANCES	
Sound power at min. speed (2010/30/EU)	32
Sound power at max. speed (2010/30/EU)	67
Noise level with boost position (dB(A) re 1 pW)	71

