
## **AKZM 8480 IX**

12NC: 852584801100

GTIN (EAN) code: 8003437832345







Product group Pećnica  Commercial code AKZM 8480 IX  Main colour of product Inox  Construction type Ugradbeni  Type of control  Type of control Hectronic  Type of control Settings -  Brončana Ne  Which kind of hobs can be controlled? -  Automatic programmes Yes  Current (A) 16  Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type Ne  Depth with open door 90 degree (mm) -  Height of the product 595  Width of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1  Trays 2	MAIN FEATURES	
Main colour of product Construction type Ugradbeni Type of control Type of control Brončana Brončana Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product Width of the product Minimum niche height Minimum niche width Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Pyrolytic Grids of the cavity  Ugradbeni Mechanical and electronic  Inox Ugradbeni Mechanical and electronic  Fedevanical and electronic  Ne Mechanical and electronic  Fedevanical and electronic  Ne Mechanical and electronic  Fed Mechanical and electronic  Fedevanical and electronic  Fedeva	Product group	Pećnica
Type of control  Type of control  Brončana  Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Depth with open door 90 degree (mm)  Height of the product  Depth of the product  Minimum niche height  Minimum niche width  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic  Grids of the cavity  Integrated Cleaning system  Puge on transland Mechanical and Mechanical and electronic  Net weight (kg)  Plug type  Ne  Depth of the product  595  Width of the product  595  Depth of the product  595  Depth of the product  596  Net weight (kg)  40  Usable volume (of cavity)  Ta	Commercial code	AKZM 8480 IX
Type of control  Type of control settings  Brončana  Ne Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Ne Depth with open door 90 degree (mm)  Height of the product  Depth of the product  Mechanical and electronic  Yes  Current (A)  16  Voltage (V)  220-240  Frequency (Hz)  50/60  Length of Electrical Supply Cord (cm)  Plug type  Ne  Depth with open door 90 degree (mm)  -  Height of the product  595  Width of the product  595  Depth of the product  564  Minimum niche height  0  Minimum niche width  0  Niche depth  0  Net weight (kg)  40  Usable volume (of cavity)  Ta  Integrated Cleaning system  Pyrolytic  Grids of the cavity	Main colour of product	Inox
Type of control  Type of control settings  Brončana  Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Depth with open door 90 degree (mm)  Height of the product  S95  Width of the product  Minimum niche height  O  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Per Me  Plug type  Re  electronic  -  electronic  Pes  Pes  Pyes  O  Net  Ne  Depth of those controlled?	Construction type	Ugradbeni
Brončana Ne Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 16 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 40 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Type of control	
Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Depth with open door 90 degree (mm)  Height of the product  S95  Width of the product  595  Width of the product  595  Depth of the product  Minimum niche height  O  Niche depth  Ne  Ves  O  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic  Grids of the cavity  1	Type of control settings	-
Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  Ne  Depth with open door 90 degree (mm)  Height of the product  S95  Width of the product  595  Width of the product  595  Depth of the product  564  Minimum niche height  0  Niche depth  Ne  Ne  Depth with open door 90 degree (mm)  73  Integrated Cleaning system  Pyrolytic  Grids of the cavity  1	Brončana	Ne
Current (A) 16  Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type Ne  Depth with open door 90 degree (mm) -  Height of the product 595  Width of the product 595  Depth of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1	Which kind of hobs can be controlled?	-
Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type Ne  Depth with open door 90 degree (mm)  Height of the product 595  Width of the product 595  Depth of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1	Automatic programmes	Yes
Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type Ne  Depth with open door 90 degree (mm) -  Height of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1	Current (A)	16
Length of Electrical Supply Cord (cm)  Plug type  Depth with open door 90 degree (mm)  Height of the product  S95  Width of the product  Depth of the product  Minimum niche height  Niche depth  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic  Grids of the cavity  Pues Poor Poor Poor Poor Poor Poor Poor Poo	Voltage (V)	220-240
Plug type Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) Usable volume (of cavity) Tall Integrated Cleaning system Pyrolytic Grids of the cavity 1	Frequency (Hz)	50/60
Depth with open door 90 degree (mm)  Height of the product  595  Width of the product  595  Depth of the product  564  Minimum niche height  0  Minimum niche width  0  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Grids of the cavity  1	Length of Electrical Supply Cord (cm)	90
Height of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1	Plug type	Ne
Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1	Depth with open door 90 degree (mm)	-
Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1	Height of the product	595
Minimum niche height     0       Minimum niche width     0       Niche depth     0       Net weight (kg)     40       Usable volume (of cavity)     73       Integrated Cleaning system     Pyrolytic       Grids of the cavity     1	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 40 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Depth of the product	564
Niche depth 0  Net weight (kg) 40  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic  Grids of the cavity 1	Minimum niche height	0
Net weight (kg)       40         Usable volume (of cavity)       73         Integrated Cleaning system       Pyrolytic         Grids of the cavity       1	Minimum niche width	0
Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic Grids of the cavity 1	Niche depth	0
Integrated Cleaning system     Pyrolytic       Grids of the cavity     1	Net weight (kg)	40
Grids of the cavity 1	Usable volume (of cavity)	73
•	Integrated Cleaning system	Pyrolytic
Trays 2	Grids of the cavity	1
	Trays	2

TECHNICAL FEATURES	
Timer	-
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Telescopic
Probe of the cavity	Ne

ENERGY LABEL	
Energy input	Electric
Type of energy of the cavity	Električna energija
Energy efficiency class - NEW (2010/30/EU)	A+
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.91
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.70