
ACM 424/IX/F

12NC: 857642438000

GTIN (EAN) code: 8003437956249







| Product group Built-in Type of control Mechanical Type of control Mechanical Type of control settings - Number of gas burners 1 Number of electric cooking zones 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cillindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 Automatic programmes | MAIN FEATURES | |
|--|---------------------------------------|------------|
| Type of control Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Plug type Gas connection Gas connection Gas connection Cillindric Width of the product Height of the product Monumer of electric warming zones Cillindric Width of the product Height of the product Monumer of electrical supply Cord (cm) Plug type No Gas connection Cillindric Width of the product Height of the product Monumer of electrical supply Monumer of electrical supple Monumer of electric electrical supple Adol Minimum niche width Monumer of electric electric electrical supple Adol Niche depth Nasse Adol Mechanical Alexander of the electric elect | Product group | Hob |
| Type of control settings - Number of gas burners 1 Number of electric cooking zones 0 Number of electric plates 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Supply Cord (cm) Cilindric Width of the product 80 Bepth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Construction type | Built-in |
| Number of gas burners 1 Number of electric cooking zones 0 Number of electric plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Type of control | Mechanical |
| Number of electric cooking zones 0 Number of electric plates 0 Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Type of control settings | - |
| Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Inox Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Plug type No Gas connection Gas connection Gilindric Width of the product Height of the product Minimum niche height Mo Niche depth Ne O O O O O O O O O O O O O | Number of gas burners | 1 |
| Number of radiant plates 0 Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Number of electric cooking zones | 0 |
| Number of halogen plates 0 Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Number of electric plates | 0 |
| Number of induction plates 0 Number of electric warming zones 0 Location of control panel Front Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Number of radiant plates | 0 |
| Number of electric warming zones Location of control panel Basic surface material Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) 100 Cungth of Electrical Supply Cord (cm) Plug type No Gas connection Cilindric Width of the product Width of the product Height of the product Minimum niche height Minimum niche width No No No No No No No No No N | Number of halogen plates | 0 |
| Location of control panel Basic surface material Inox Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) 100 Current of Electrical Supply Cord (cm) Plug type No Gas connection Cilindric Width of the product Width of the product Depth of the product Minimum niche height Minimum niche width No Niche depth No Residuation Front Inox Ino | Number of induction plates | 0 |
| Basic surface material Inox Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Number of electric warming zones | 0 |
| Main colour of product Inox Electrical connection rating (W) 0 Gas connection rating (W) 3700 Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Location of control panel | Front |
| Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection Cilindric Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth No O O O Niche depth No O Niche depth (kg) O O O O O O O O O O O O O | Basic surface material | Inox |
| Gas connection rating (W) Current (A) Voltage (V) Erequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection Cilindric Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Na 3700 Cilindric Au Au Au Au Minimum niche width Au Au Au Minimum niche width Au Au Niche depth Niche depth Sa Net weight (kg) | Main colour of product | Inox |
| Current (A) - Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Electrical connection rating (W) | 0 |
| Voltage (V) 230 Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Gas connection rating (W) | 3700 |
| Frequency (Hz) 50 Length of Electrical Supply Cord (cm) - Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 50 | Current (A) | - |
| Length of Electrical Supply Cord (cm) Plug type No Gas connection Cilindric Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth No Plug type No Niche depth No No No No No No No No No N | Voltage (V) | 230 |
| Plug type No Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Frequency (Hz) | 50 |
| Gas connection Cilindric Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Length of Electrical Supply Cord (cm) | - |
| Width of the product 400 Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Plug type | No |
| Height of the product 80 Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Gas connection | Cilindric |
| Depth of the product 400 Minimum niche height 80 Minimum niche width 400 Niche depth 388 Net weight (kg) 20 | Width of the product | 400 |
| Minimum niche height80Minimum niche width400Niche depth388Net weight (kg)20 | Height of the product | 80 |
| Minimum niche width400Niche depth388Net weight (kg)20 | Depth of the product | 400 |
| Niche depth 388 Net weight (kg) 20 | Minimum niche height | 80 |
| Net weight (kg) 20 | Minimum niche width | 400 |
| - , -, | Niche depth | 388 |
| Automatic programmes No | Net weight (kg) | 20 |
| | Automatic programmes | No |

| TECHNICAL FEATURES | |
|-------------------------|---------|
| Power on indicator | - |
| Number of indicators | - |
| Type of regulation | N/A |
| Type of lid | - |
| Residual heat indicator | Without |
| Main on/off switch | No |
| Safety device | - |
| Timer | - |

| PERFORMANCES | |
|--------------|-----|
| Energy input | Gas |