

W7 MW561 UK

12NC/Fx: 859991544490

GTIN (EAN) code: 8003437396120

DIMENSION	MEAS	URI
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	450	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	453	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	453	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm
Space in front, which is required to install bottom trim	8	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm ²
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	0	mm
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm ²
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm ²
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm ²
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm ²

Width of the front 20 mm Auximum depth all protruding elements, e.g. handles, controls 42 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 7 mm Frontal handle thickness 18 mm House of the product body 447 mm MIN Height of the product body 447 mm MIN Height of the product body 533 mm Frontal handle width 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 1 mm Projection of the rear flap in relation to bearing area 1 mm Maximum angle when flap door is opened totally. At the side where the hinge is mounted 1 mm Maximum angle when flap door is opened totally. At the side where the hinge is mounted 1 mm Maximum angle when door is opened totally and mm Appliance of the rear floor of the note to the front end of the freespace of the retrace 1 do mm Maximum angle when flap door is opened totally. At the side where the hinge is mounted 1 mm Depth from front end of the niche to the front end of the freespace of the retrace 1 do mm Appliance of the projection of opened front at the side where the hinge is fixed 1 mm Projection of the niche to the front end of the freespace of the retrace 1 do mm Appliance of the projection of the niche to the front end of the freespace of the retrace 1 do mm	DIMENSION		EASURE	
Width of the front 20 mm Maximum depth all protruding elements, e.g. handles, controls 42 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 18 mm Frontal handle thickness 18 mm MIN Height of the product body 447 mm MAX Height of the product body 447 mm Mix Height of the product body 553 mm Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter minimum air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter maximum air outlet New projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Depth from front end of the niche to the front end of the freespace of the retrace Depth from front end of the niche to the front end of the freespace of the retrace	APPLIANCE			
Depth of the front Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 18 mm Frontal handle width 561 mm MIN Height of the product body MAX Height of the product body Width of the product body Width of the product body S35 mm Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter maximum air outlet Appliance Side swing door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Depth from the of the niche to the front end of the freespace of the retrace Depth front font end of the niche to the front end of the freespace of the retrace 10 mm Maximum angle when door is opened totally Appliance Side swing door Depth front front end of the niche to the front end of the freespace of the retrace	Height of the front	455	mm	
Maximum depth all protruding elements, e.g. handles, controls Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 10 MIN Height of the product body MAX Height of the product body Width of the product body Width of the product body Space in front, which is required to guarantee full operability. The most protruding part gives this admension Hind height of the product body MAX Height of the product body 447 MIN Height of the product body Width of the product body Space in the product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter maximum air outlet Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the inche to the front end of the freespace of the retrace Maximum angle when door is opened totally Appliance other	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness Frontal handle thickness Frontal handle width MIN Height of the product body MAX Height of the product body MAX Height of the product body More product bod	Depth of the front	20	mm	
neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 325 mm Frontal handle thickness 18 mm Frontal handle width 561 mm MIN Height of the product body 447 mm Width of the product body 447 mm Width of the product body 553 mm Depth of the product body 553 mm Minimum height from bottom line hood to top line air outlet 00 mm Maximum height from bottom line hood to top line air outlet 01 mm Diameter minimum air outlet 02 mm Diameter maximum air outlet 03 mm Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm Appliance other	Maximum depth all protruding elements, e.g. handles, controls	42	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 325 mm Frontal handle thickness 18 mm Frontal handle width 561 mm MIN Height of the product body 447 mm MAX Height of the product body 553 mm Depth of the product body 553 mm Depth of the product body 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Side swing door Lateral projection of opened flap in relation to bearing area Maximum angle when flap door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	, , , , , , , , , , , , , , , , , , ,	0	mm	
appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 18 Frontal handle width 561 MIN Height of the product body 447 MAX Height of the product body 553 mr Width of the product body 553 mr Depth of the product body 554 Minimum height from bottom line hood to top line air outlet 0 Maximum height from bottom line hood to top line air outlet 0 Diameter maximum air outlet 0 Diameter maximum air outlet 0 Indicates measure between center of air outlet hole and rear wall 0 Projection of the rear flap in relation to bearing area 1 Height tube connection for air outlet Appliance Flap door Projection of the opened flap in relation to bearing area 4 Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is mounted 1 Depth from front end of the niche to the front end of the freespace of the retrace 140 mr Appliance other Depth from front end of the niche to the front end of the freespace of the retrace	Projection of front in relation to housing of appliance	10	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 7 rontal handle thickness 18 mm Frontal handle width 561 mm MIN Height of the product body 447 mm MAX Height of the product body 553 mm Depth of the product body 554 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	· · · · · · · · · · · · · · · · · · ·	0	mm	
dimension Height from bearing area of appliances and lower handle Frontal handle thickness 18 mm Frontal handle width 561 mm MIN Height of the product body 447 mm Width of the product body 553 mm Depth of the product body 553 mm Full depth of product excluding protruding interface elements 554 mm Maximum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm Appliance other	When product panel is missing, set to 0	95	mm	
Frontal handle thickness Frontal handle width Frontal handle Front		348	mm	
Frontal handle width 561 mm MIN Height of the product body 447 mm MAX Height of the product body 553 mm Width of the product body 553 mm Depth of the product body 553 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Diameter maximum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally 85 mm Appliance Side swing door Lateral projection of opened front at the side where the hinge is mounted 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm	Height from bearing area of appliances and lower handle	325	mm	
MIN Height of the product body MAX Height of the product body Width of the product body Depth of the product body S53 mm Full depth of product excluding protruding interface elements S54 mm Minimum height from bottom line hood to top line air outlet O mm Maximum height from bottom line hood to top line air outlet O mm Diameter minimum air outlet O mm Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Frontal handle thickness	18	mm	
MAX Height of the product body Width of the product body Depth of the product body 535 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area 0 mm Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Frontal handle width	561	mm	
Width of the product body Depth of the product body Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter minimum air outlet Diameter maximum air outlet Diameter air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter air outlet Diameter air outlet Diameter maximum air outlet Diameter air	MIN Height of the product body	447	mm	
Depth of the product body Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Diameter maximum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 0 mm Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	MAX Height of the product body	447	mm	
Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 0 mm Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Width of the product body	553	mm	
Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter minimum air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter maximum air outlet No mm Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Depth of the product body	535	mm	
Maximum height from bottom line hood to top line air outlet Diameter minimum air outlet Diameter maximum air outlet O mm Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Full depth of product excluding protruding interface elements	554	mm	
Diameter minimum air outlet Diameter maximum air outlet Diameter maximum air outlet Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Minimum height from bottom line hood to top line air outlet	0	mm	
Diameter maximum air outlet Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Maximum height from bottom line hood to top line air outlet	0	mm	
Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area 0 mm Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Diameter minimum air outlet	0	mm	
Projection of the rear flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Diameter maximum air outlet	0	mm	
Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Indicates measure between center of air outlet hole and rear wall	0	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Projection of the rear flap in relation to bearing area	0	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally 85 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Height tube connection for air outlet	0	mm	
Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No	" -		
Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Appliance Flap door			
Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally O mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Projection of the opened flap in relation to bearing area	6	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed O mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Maximum angle when flap door is opened totally	85	mm	
mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Appliance Side swing door			
Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm		s 0	mm	
Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Maximum angle when door is opened totally	0	mm	
·	Appliance other			
Height from niche to bottom end of freespace for the retrace 391 mm	Depth from front end of the niche to the front end of the freespace of the retrace	140	mm	
	Height from niche to bottom end of freespace for the retrace	391	mm	