
IO 258HU X UK

12NC: F170530

GTIN (EAN) code: 8050147705308







roduct group commercial code lain colour of product construction type type of control type of control settings re any hobs controls integrated? thich kind of hobs can be controlled? utomatic programmes urrent (A) coltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product thidth of the product linimum niche height linimum niche width iche depth et weight (kg)	MAIN FEATURES		
lain colour of product construction type //pe of control //pe of control settings re any hobs controls integrated? //hich kind of hobs can be controlled? utomatic programmes urrent (A) coltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product //idth of the product linimum niche height linimum niche width iche depth	0ven		
onstruction type /pe of control /pe of control settings re any hobs controls integrated? /hich kind of hobs can be controlled? utomatic programmes urrent (A) oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product /idth of the product linimum niche height linimum niche width iche depth	IO 258HU X UK		
ype of control ype of control settings re any hobs controls integrated? //hich kind of hobs can be controlled? utomatic programmes urrent (A) oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product //idth of the product linimum niche height linimum niche width iche depth	Inox		
ype of control settings re any hobs controls integrated? //hich kind of hobs can be controlled? utomatic programmes urrent (A) oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product //idth of the product linimum niche height linimum niche width iche depth	Built-in		
re any hobs controls integrated? /hich kind of hobs can be controlled? utomatic programmes urrent (A) oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product /idth of the product epth of the product linimum niche height linimum niche width iche depth	Electronic		
/hich kind of hobs can be controlled? utomatic programmes urrent (A) oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product //idth of the product epth of the product linimum niche height linimum niche width iche depth	-		
utomatic programmes urrent (A) oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product /idth of the product epth of the product linimum niche height linimum niche width iche depth	No		
urrent (A) oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product ridth of the product epth of the product linimum niche height linimum niche width iche depth	-		
oltage (V) requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product //idth of the product epth of the product linimum niche height linimum niche width iche depth	Yes		
requency (Hz) ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product //idth of the product linimum niche height linimum niche width iche depth	13		
ength of Electrical Supply Cord (cm) lug type epth with open door 90 degree (mm) eight of the product //idth of the product epth of the product linimum niche height linimum niche width iche depth	220-240		
lug type epth with open door 90 degree (mm) eight of the product /idth of the product epth of the product linimum niche height linimum niche width iche depth	50/60		
epth with open door 90 degree (mm) eight of the product lidth of the product epth of the product linimum niche height linimum niche width iche depth	100		
eight of the product /idth of the product epth of the product linimum niche height linimum niche width iche depth	UK		
lidth of the product epth of the product linimum niche height linimum niche width iche depth	-		
epth of the product linimum niche height linimum niche width iche depth	595		
linimum niche height linimum niche width iche depth	595		
linimum niche width iche depth	551		
iche depth	0		
•	0		
et weight (kg)	0		
	27.1		
sable volume (of cavity)	71		
ntegrated Cleaning system	Hydrolytic		
rids of the cavity	2		
rays	1		

TECHNICAL FEATURES	
Timer	Yes
Time control	Electronic
Time-setting options	Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Front left
Oven guides of the cavity	Grids
Probe of the cavity	No

PERFORMANCES	
Energy input	Electric
Type of energy of the cavity	Electricity
Energy efficiency class - NEW (2010/30/EU)	A+
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.89
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.69