



# ARG 146/A+/LA.1

# 12NC/Fx: 859991556250

# GTIN (EAN) code: 8003437042799

DIMENSION	MEASURE	
<b>WOODEN CABINET - Overall Wooden Cabinet - BI</b>		
01. Height MIN of the tall cabinet Niche, including all required space for installation or ventilation (HMIN_T)	820	mm
02. Height MAX of the tall cabinet Niche, including all required space for installation or ventilation (HMAN_T)	890	mm
03. Width MIN of the tall cabinet Niche, including all required space for installation or ventilation (WMIN_T)	600	mm
04. Width MAX of the tall cabinet Niche, including all required space for installation or ventilation (WMAN_T)	600	mm
05. Depth of the tall cabinet Niche, including all required space for installation or ventilation (DN_T)	550	mm
06. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)	820	
07. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)	890	
08. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)	599	
09. Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	601	
10. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	550	
11. Indicates whether a ventilation opening is needed or not. Default is "N"	No	
12. Appliance can be used as base for other appliances from the same manufacturer. Default is "N"	Yes	
<b>WOODEN CABINET - Door – Drawer</b>		
13. Height MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (HMIF)	645	mm
14. Width MIN Decorative Front, if appliance has more than one front, only the most bottom left front is described here (WMIF)	586	mm
15. Weight/Thickness of the decorative bottom front panel of the Kitchen manufacturer needs (essential)	Yes	
16. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	0	kg
17. Thickness MIN Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMIF)	0	mm
18. Thickness MAX Decorative Front, if appliance has more than one front only the most bottom left front is described here(TMAF)	0	mm
<b>Additional Fronts (2 doors)</b>		
19. Height MIN Decorative Front, when appliance has more than one front, upper front is described here (HMIFU)	0	mm
20. Width MIN Decorative Front, when appliance has more than one front, upper front is described here (WMIFU)	0	mm
21. Weight/Thickness of the decorative upper front panel of the Kitchen manufacturer needs (essential)	Yes	
22. Weight MAX of the decorative upper front panel of the Kitchen manufacturer (WEMAFU)	0	kg
23. Thickness MIN Decorative Front, when appliance has more than one front, upper front is described here (TMIFU)	0	mm
24. Thickness MAX Decorative Front, when appliance has more than one front, upper front is described here (TMAFU)	0	mm

DIMENSION	MEASURE	
<b>APPLIANCE</b>		
<b>Overall Appliance</b>		
01. Height MIN Product, watch the detail drawing for the exact position of the dimension line (HMIP)	819	mm
02. Height MAX product, watch the detail drawing for the exact position of the dimension line (HMAP)	889	mm
03. Width product, watch the detail drawing for the exact position of the dimension line (WP)	597	mm
04. Depth product without front, watch the detail drawing for the exact position of the dimension line (DP)	500	mm
05. Depth product, watch the detail drawing for the exact position of the dimension line (D)	545	mm
06. Depth MIN plinth return front (DMIPRF)	0	mm
07. Depth MAX plinth return front (DMAPRF)	93	mm
08. Height MIN Plinth return. This dimension is taken by minimum appliance height (HMIPR)	198	mm
09. Height MAX Plinth return. This dimension is taken at minimum appliance height (HMAPR)	268	mm
<b>Door or Drawer</b>		
10. Height front. When appliance has more than one front, only the most bottom left front is described here (HF)	0	mm
11. Width front. When appliance has more than one front, only the most bottom left front is described here (WF)	597	mm
12. Depth front (DF)	0	mm
13. Maximum depth all protruding elements, e.g. handles, controls (DC)	0	mm
14. Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90° (CC)	0	mm
15. Projection of front in relation to housing of appliance (FPT)	20	mm
16. Projection of front in relation to bearing area of the appliance. Taken at MIN height of appliance if adjustable height(FPB)	0	mm
17. Height Product Panel. When product panel is missing, set to 0 (HMAPP)	35	mm
18. Lateral projection of front including controls when door is opened totally. At the side where the hinge is mounted (FPOD)	0	mm
19. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	638	mm
20. Lateral projection of opened front at the side where the hinge is fixed (FPD)	0	mm
21. Door hinge positioning and tipology		Right-changeable
22. Type of preparation to fix the cover door		Fixed mounting
23. Maximum angle when door is opened totally (AOD)	105	°
24. Maximum thickness of the upper front panel (TUFP)	4	mm
<b>Additional Fronts (2 doors)</b>		
25. Height front, when appliance has more than one front, upper front is described here (HUF)	0	mm
26. Width front, when appliance has more than one front, upper front is described here (WUF)	0	mm
27. Useful space between the 2 doors, including hinges size (HMAFG)	20	mm
28. Distance between the bottom of the product and the center line between the fridge doors (HFG)	0	mm

<b>TALL WOODEN CABINET - Vent-shaft incoming</b>		
25. Indicates the position of the freespace for the incoming airflow, tall wooden cabinet	-	
26. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TI)	0	mm
27. Ventilation cavity minimum, tall wooden cabinet (VC_TI)	0	cm <sup>2</sup>
<b>TALL WOODEN CABINET - Vent-shaft outgoing</b>		
28. Indicates the position of the freespace for the outgoing airflow, tall wooden cabinet	-	
29. Clearance MIN Ventilation, tall wooden cabinet (CMIV_TO)	50	mm
30. Ventilation cavity minimum, tall wooden cabinet (VC_TO)	0	cm <sup>2</sup>
<b>BASE WOODEN CABINET - Vent-shaft incoming</b>		
31. Indicates the position of the freespace for the incoming airflow, base wooden cabinet	-	
32. Clearance MIN Ventilation, base wooden cabinet (CMIV_BI)	0	mm
33. Ventilation cavity minimum, base wooden cabinet (VC_BI)	0	cm <sup>2</sup>
<b>BASE WOODEN CABINET - Vent-shaft outgoing</b>		
34. Indicates the position of the freespace for the outgoing airflow, base wooden cabinet	-	
35. Clearance MIN Ventilation, base wooden cabinet (CMIV_BO)	0	mm
36. Ventilation cavity minimum, base wooden cabinet (VC_BO)	0	cm <sup>2</sup>