
## H0I98PT2SBUK

12NC: F168258

GTIN (EAN) code: 5054645682584







Product group Oven  Commercial code H0198PT2SBUK  Main colour of product Black  Construction type Built-in  Type of control Electronic  Type of control settings - No  Which kind of hobs can be controlled? - Automatic programmes  Current (A) 13  Voltage (V) 220-240  Frequency (Hz) 50  Length of electrical supply cord (cm) 130  Plug type UK  Depth with open door 90 degree (mm) - Width of the product 597  Width of the product 597  Width of the product 564  Minimum niche height 583  Minimum niche width 560  Niche depth 550  Net weight (kg) 39.6  Usable volume (of cavity)  Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2  Trays 2	MAIN FEATURES	
Main colour of product  Construction type Built-in Type of control Type of control Type of control settings Are any hobs controls integrated? No Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of electrical supply cord (cm) Plug type UK Depth with open door 90 degree (mm) - Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Type Oscillation Shark Tyes  Built-in Black Built-in Bu	Product group	Oven
Construction type Type of control Type of control Type of control settings Are any hobs controls integrated? No Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of electrical supply cord (cm) Plug type UK Depth with open door 90 degree (mm)	Commercial code	HOI98PT2SBUK
Type of control Type of control settings Are any hobs controls integrated? Which kind of hobs can be controlled? Automatic programmes Current (A) Voltage (V) Frequency (Hz) Length of electrical supply cord (cm) Plug type UK Depth with open door 90 degree (mm) Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Niche depth Niche depth Niche depth Vigen or cavity Type of control Electronic Flectronic  1 No Electronic Flectronic	Main colour of product	Black
Type of control settings  Are any hobs controls integrated?  Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of electrical supply cord (cm)  Plug type  UK  Depth with open door 90 degree (mm)  Height of the product  Depth of the product  S97  Width of the product  Minimum niche height  Minimum niche width  Niche depth  S50  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic+Hydrolytic  Grids of the cavity  2	Construction type	Built-in
Are any hobs controls integrated?  Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of electrical supply cord (cm)  Plug type  UK  Depth with open door 90 degree (mm)  Height of the product  Depth of the product  S97  Width of the product  Depth of the product  Minimum niche height  S83  Minimum niche width  Niche depth  S50  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic+Hydrolytic  Grids of the cavity  2	Type of control	Electronic
Which kind of hobs can be controlled?  Automatic programmes  Yes  Current (A)  Voltage (V)  Frequency (Hz)  Length of electrical supply cord (cm)  Plug type  UK  Depth with open door 90 degree (mm)  Height of the product  597  Width of the product  595  Depth of the product  596  Minimum niche height  583  Minimum niche width  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic+Hydrolytic  Grids of the cavity  2	Type of control settings	-
Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of electrical supply cord (cm)  Plug type  UK  Depth with open door 90 degree (mm)  Height of the product  597  Width of the product  595  Depth of the product  596  Minimum niche height  583  Minimum niche width  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Yes  Yes  13  13  11  12  12  130  130  130  130	Are any hobs controls integrated?	No
Current (A)         13           Voltage (V)         220-240           Frequency (Hz)         50           Length of electrical supply cord (cm)         130           Plug type         UK           Depth with open door 90 degree (mm)         -           Height of the product         597           Width of the product         595           Depth of the product         564           Minimum niche height         583           Minimum niche width         560           Niche depth         550           Net weight (kg)         39.6           Usable volume (of cavity)         73           Integrated Cleaning system         Pyrolytic+Hydrolytic           Grids of the cavity         2	Which kind of hobs can be controlled?	-
Voltage (V)  Frequency (Hz)  Length of electrical supply cord (cm)  Plug type  UK  Depth with open door 90 degree (mm)  Height of the product  Septimal Sept	Automatic programmes	Yes
Frequency (Hz) 50  Length of electrical supply cord (cm) 130  Plug type UK  Depth with open door 90 degree (mm) -  Height of the product 597  Width of the product 595  Depth of the product 564  Minimum niche height 583  Minimum niche width 560  Niche depth 550  Net weight (kg) 39.6  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Current (A)	13
Length of electrical supply cord (cm)  Plug type  Depth with open door 90 degree (mm)  Height of the product  S97  Width of the product  Depth of the product  Minimum niche height  S83  Minimum niche width  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic+Hydrolytic  Grids of the cavity  130  130  130  130  130  140  150  150  150  150  150  150  15	Voltage (V)	220-240
Plug type  Depth with open door 90 degree (mm)  Height of the product  S97  Width of the product  Depth of the product  Minimum niche height  Minimum niche width  S60  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Pyrolytic+Hydrolytic  Grids of the cavity  2	Frequency (Hz)	50
Depth with open door 90 degree (mm)  Height of the product  597  Width of the product  595  Depth of the product  564  Minimum niche height  583  Minimum niche width  560  Niche depth  550  Net weight (kg)  39.6  Usable volume (of cavity)  Talegrated Cleaning system  Pyrolytic+Hydrolytic  Grids of the cavity  2	Length of electrical supply cord (cm)	130
Height of the product 597  Width of the product 595  Depth of the product 564  Minimum niche height 583  Minimum niche width 560  Niche depth 550  Net weight (kg) 39.6  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Plug type	UK
Width of the product 595  Depth of the product 564  Minimum niche height 583  Minimum niche width 560  Niche depth 550  Net weight (kg) 39.6  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic+Hydrolytic  Grids of the cavity 2	Depth with open door 90 degree (mm)	-
Depth of the product 564  Minimum niche height 583  Minimum niche width 560  Niche depth 550  Net weight (kg) 39.6  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic+Hydrolytic  Grids of the cavity 2	Height of the product	597
Minimum niche height583Minimum niche width560Niche depth550Net weight (kg)39.6Usable volume (of cavity)73Integrated Cleaning systemPyrolytic+HydrolyticGrids of the cavity2	Width of the product	595
Minimum niche width 560 Niche depth 550 Net weight (kg) 39.6 Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Depth of the product	564
Niche depth 550  Net weight (kg) 39.6  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic+Hydrolytic  Grids of the cavity 2	Minimum niche height	583
Net weight (kg) 39.6  Usable volume (of cavity) 73  Integrated Cleaning system Pyrolytic+Hydrolytic  Grids of the cavity 2	Minimum niche width	560
Usable volume (of cavity) 73 Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Niche depth	550
Integrated Cleaning system Pyrolytic+Hydrolytic Grids of the cavity 2	Net weight (kg)	39.6
Grids of the cavity 2	Usable volume (of cavity)	73
•	Integrated Cleaning system	Pyrolytic+Hydrolytic
Trays 2	Grids of the cavity	2
	Trays	2

TECHNICAL FEATURES	
Timer	Yes
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Telescopic
Probe of the cavity	No

PERFORMANCES		
Energy input	Electric	
Type of energy of the cavity	Electricity	
Energy efficiency class - NEW (2010/30/EU)	A+	
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.64	
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.87	