

## WOI5S8CM1SBA

## 12NC/Fx: 859991685160

## GTIN (EAN) code: 8003437836770

<b>VERALL CABINET</b> N Height of the wall cabinet niche, including all required space for installation or ventilation N Height of the tall cabinet niche, including all required space for installation or ventilation	0	
N Height of the tall cabinet niche, including all required space for installation or ventilation	0	
		mm
	583	mm
N Height of the base cabinet niche, including all required space for installation or ventilation	595	mm
X Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
X Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
X Height of the base cabinet niche, including all required space for installation or ventilation	n 596	mm
N Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
N Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
N Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
X Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
X Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
X Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
N Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
N Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm
N Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm
ace in front, which is required to install bottom trim	10	mm
icates whether a ventilation opening is needed or not. Default is "N"	Yes	
ALL CABINET (vent-shaft incoming)		
icates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
nimum space or inbound ventilation (wall cabinet)	0	mm
nimum area for inbound ventilation cavity (wall cabinet)	0	cm
ALL CABINET (vent-shaft outgoing)		
licates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
nimum space or outbound ventilation (wall cabinet)	0	mm
nimum area for outbound ventilation cavity (wall cabinet)	0	cm
LL CABINET (vent-shaft incoming)		
licates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
nimum space for inbound ventilation (tall cabinet)	30	mm
nimum area for inbound ventilation cavity (tall cabinet)	150	cm
LL CABINET (vent-shaft outgoing)		•
icates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
nimum space for outbound ventilation (tall cabinet)	0	mm
nimum area for outbound ventilation cavity (tall cabinet)	150	cm
SE CABINET (vent-shaft incoming)	100	om
licates the position of the freespace for the inbound airflow (base cabinet)	Rear	
nimum space for inbound ventilation (base cabinet)	30	mm
nimum area for inbound ventilation cavity (base cabinet)	150	cm
SE CABINET (vent-shaft outgoing)	150	UII
licates the position of the freespace for the outbound airflow (base cabinet)	Rear	
nimum space for outbound ventilation (base cabinet)	0	mm
nimum area for outbound ventilation cavity (base cabinet)	150	cm <sup>2</sup>

DIMENSION ME		EASURE	
APPLIANCE			
Height of the front	597	mm	
Width of the front	595	mm	
Depth of the front	20	mm	
Maximum depth all protruding elements, e.g. handles, controls	41	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	41	mm	
Projection of front in relation to housing of appliance	18	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	7	mm	
When product panel is missing, set to 0	97	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	462	mm	
Height from bearing area of appliances and lower handle	465	mm	
Frontal handle thickness	41	mm	
Frontal handle width	532	mm	
MIN Height of the product body	572	mm	
MAX Height of the product body	572	mm	
Width of the product body	546	mm	
Depth of the product body	543	mm	
Full depth of product excluding protruding interface elements	564	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Appliance Flap door			
Projection of the opened flap in relation to bearing area	0	mm	
Maximum angle when flap door is opened totally	89	mm	
Appliance Side swing door			
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mm	
Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Maximum angle when door is opened totally	0	mm	
Appliance other			
Depth from front end of the niche to the front end of the freespace of the retrace	345	mm	
Height from niche to bottom end of freespace for the retrace	537	mm	