
HEX9024DCFF2

12NC: F168756

GTIN (EAN) code: 5054645687565







Product group Construction type Built-in Type of control Electronic Type of control Electronic Type of control settings Number of gas burners O Number of electric cooking zones Number of electric plates Number of radiant plates Number of induction plates Number of electric warming zones Number of electric warming zones O Number of of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) 48 Voltage (V) Prequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche width Net weight (kg) Net weight (kg) Net weight (kg) Automatic programmes	MAIN FEATURES		
Type of control Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection Moderate of the product Beach Electrical connection N/A Width of the product Depth of the product Minimum niche width Net weight (kg) Net weight (kg) Electronic O Cornent A Electronic Ceramic Glass Ceramic Glass No Ceramic Glass No Ceramic Glass No Ceramic Glass No Ceramic Glass Black Electrical connection rating (W) 11100 O 48 Voltage (V) 120-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) Folia (Time to the product) Solo (Cornel to the product) Solo (Co	Product group	Hob	
Type of control settings Number of gas burners Number of electric cooking zones Number of electric plates Number of radiant plates Number of halogen plates Number of induction plates Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Prequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Depth of the product Minimum niche width Net weight (kg) Net weight (kg) Net weight (kg) 18	Construction type	Built-in	
Number of gas burners 0 Number of electric cooking zones 5 Number of electric plates 0 Number of halogen plates 0 Number of induction plates 5 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 48 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type No Gas connection N/A Width of the product 54 Depth of the product 54 Depth of the product 570 Minimum niche height 880 Niche depth 490 Net weight (kg) 18	Type of control	Electronic	
Number of electric cooking zones5Number of electric plates0Number of radiant plates0Number of induction plates5Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)0Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)150Plug typeNoGas connectionN/AWidth of the product54Depth of the product570Minimum niche height28Minimum niche width880Niche depth490Net weight (kg)18	Type of control settings	-	
Number of electric plates0Number of radiant plates0Number of halogen plates0Number of induction plates5Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)0Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)150Plug typeNoGas connectionN/AWidth of the product54Depth of the product570Minimum niche height28Minimum niche width880Niche depth490Net weight (kg)18	Number of gas burners	0	
Number of radiant plates 0 Number of induction plates 5 Number of induction plates 5 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 48 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type No Gas connection N/A Width of the product 54 Depth of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Number of electric cooking zones	5	
Number of halogen plates 0 Number of induction plates 5 Number of electric warming zones 0 Location of control panel Front Basic surface material Ceramic Glass Main colour of product Black Electrical connection rating (W) 0 Gas connection rating (W) 0 Gas type N/A Current (A) 48 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type No Gas connection N/A Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Number of electric plates	0	
Number of induction plates5Number of electric warming zones0Location of control panelFrontBasic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)11100Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)150Plug typeNoGas connectionN/AWidth of the product1000Height of the product54Depth of the product570Minimum niche height28Minimum niche width880Niche depth490Net weight (kg)18	Number of radiant plates	0	
Number of electric warming zones Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) Front Black 1100 0 0 0 0 0 0 0 0 0 0 0	Number of halogen plates	0	
Location of control panel Basic surface material Ceramic Glass Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Minimum niche height Associated ass	Number of induction plates	5	
Basic surface materialCeramic GlassMain colour of productBlackElectrical connection rating (W)11100Gas connection rating (W)0Gas typeN/ACurrent (A)48Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)150Plug typeNoGas connectionN/AWidth of the product1000Height of the product54Depth of the product570Minimum niche height28Minimum niche width880Niche depth490Net weight (kg)18	Number of electric warming zones	0	
Main colour of product Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche height Associated ass	Location of control panel	Front	
Electrical connection rating (W) Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Depth of the product Minimum niche height Associated width Miche depth Net weight (kg) 11100 11100 1200	Basic surface material	Ceramic Glass	
Gas connection rating (W) Gas type N/A Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) O N/A O N/A N/A N/A Minimum niche width N/A Net weight (kg) N/A N/A N/A N/A N/A N/A N/A N/	Main colour of product	Black	
Gas type N/A Current (A) 48 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type No Gas connection N/A Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Electrical connection rating (W)	11100	
Current (A) 48 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type No Gas connection N/A Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Gas connection rating (W)	0	
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type No Gas connection N/A Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Gas type	N/A	
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 150 Plug type No Gas connection N/A Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth (kg) 18	Current (A)	48	
Length of Electrical Supply Cord (cm) Plug type No Gas connection N/A Width of the product Height of the product Depth of the product Minimum niche height Minimum niche width Niche depth Net weight (kg) 150 N/A 1000 N/A N/A N/A 1000 N/A 1000 N/A N/A N/A 1000 N/A N/A N/A N/A N/A N/A N/A	Voltage (V)	220-240	
Plug type No Gas connection N/A Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Frequency (Hz)	50/60	
Gas connection N/A Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Length of Electrical Supply Cord (cm)	150	
Width of the product 1000 Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Plug type	No	
Height of the product 54 Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Gas connection	N/A	
Depth of the product 570 Minimum niche height 28 Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Width of the product	1000	
Minimum niche height28Minimum niche width880Niche depth490Net weight (kg)18	Height of the product	54	
Minimum niche width 880 Niche depth 490 Net weight (kg) 18	Depth of the product	570	
Niche depth 490 Net weight (kg) 18	Minimum niche height	28	
Net weight (kg) 18	Minimum niche width	880	
· (),	Niche depth	490	
Automatic programmes Yes	Net weight (kg)	18	
	Automatic programmes	Yes	

TECHNICAL FEAT	TURES
Power on indicator	Yes
Number of indicators	5
Type of regulation	Induction
Type of lid	Without
Residual heat indicator	Separate
Main on/off switch	Yes
Safety device	-
Timer	Yes

PERFORMANCES	
Energy input	Electric