

ACM 822/NE

12NC: 859991007670

GTIN (EAN) code: 8003437826238







- 4 induction cooking zones
- Residual heat indicator
- Child lock
- On/Off Switch
- 60 cm hob
- Timer
- Touch control (AKO, Arthemis 2)
- Black Glass Hob
- 1 Booster
- 4 Plate on Indicator
- Total power declared: 7 kW
- Power on indicator
- Supply cord included
- Power manager: maximum power setting 2,5 kW/4 kW/6 kW/7,4 kW
- Frameless
- Dimensions HxWxD: 56x580x510 mm

Whirlpool induction glass-ceramic hob - ACM 822/NE

4 induction rings. this Whirlpool induction glass-ceramic Hob features: An elegant technology, that heats the pan, not the hob, reducing energy dispersion and providing perfect cooking results. Electric power supply.



Power management

Outstanding energy efficiency. With the Power Management function, you set the hob's power level, to avoid the risk of overloading the power supply in your home.



Booster

Enjoy super fast boiling times with the Booster cooking zone.



Booster 3Kw

Enjoy ideal results, faster. This Whirlpool Hob features a 3Kw booster for faster, effective heating results.



Front Controls

Complete control over your cooking. Easily accessible and genuinely intuitive, the controls are conveniently positioned on the front panel of your hob, providing a frictionless cooking experience.



Induction technology

Faster, energy-efficient cooking. Induction technology heats the pan, not the hob, reducing energy dispersion by 10%, and providing perfect cooking results.

ACM 822/NE

12NC: 859991007670

GTIN (EAN) code: 8003437826238



| MAIN FEATURE | |
|---------------------------------------|---------------------------|
| Product group | Hob |
| Construction type | Built-in |
| Type of control | Electronic |
| Type of control settings | - |
| Number of gas burners | 0 |
| Number of electric cooking zones | 4 |
| Number of electric plates | 0 |
| Number of radiant plates | 0 |
| Number of halogen plates | 0 |
| Number of induction plates | 4 |
| Number of electric warming zones | 0 |
| Location of control panel | Front |
| Basic surface material | Glass |
| Main colour of product | Black |
| Electrical connection rating (W) | 6500 |
| Gas connection rating (W) | 0 |
| Current (A) | 28,1 |
| Voltage (V) | 230 |
| Frequency (Hz) | 50/60 |
| Length of Electrical Supply Cord (cm) | 120 |
| Plug type | No |
| Gas connection | N/A |
| Width of the product | 580 |
| Height of the product | 56 |
| Depth of the product | 510 |
| Minimum niche height | 30 |
| Minimum niche width | 560 |
| Niche depth | 490 |
| Net weight (kg) | 12.5 |
| Automatic programmes | No No |
| | |
| TECHNICAL FEATU | IRES |
| Power on indicator | Yes |
| Number of indicators | 4 |
| Type of regulation | Stepless energy regulated |
| Type of lid | Without |
| Residual heat indicator | Separate |
| Main on/off switch | Yes |
| Safety device | - |
| Timer | Yes |
| | • |
| PERFORMANCE | S . |
| Energy input | Electric |