
AKP 738 IX

12NC: 857773801500

GTIN (EAN) code: 8003437937712







Product group Pećnica Commercial code AKP 738 IX Main colour of product Inox Construction type Ugradbeni Type of control Mechanical Type of control Settings - Brončana Ne Which kind of hobs can be controlled? - Automatic programmes Ne Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity 1 Trays 2	MAIN FEATURES	
Main colour of product Construction type Ugradbeni Type of control Type of control Brončana Ne Which kind of hobs can be controlled? Automatic programmes Ne Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product Minimum niche height Ne Netweight (kg) Usable volume (of cavity) Netweight (kg) Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity Index and mechanical Inox Inox	Product group	Pećnica
Construction type Type of control Type of control Type of control Settings Frončana Re Which kind of hobs can be controlled? Automatic programmes Re Current (A) 13 Voltage (V) 220-240 Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Re Depth with open door 90 degree (mm)	Commercial code	AKP 738 IX
Type of control Type of control settings Brončana Ne Which kind of hobs can be controlled? Automatic programmes Ne Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product Seps Width of the product Seps Width of the product Mechanical Ne Me 220-240 Frequency (Hz) So/60 Length of Electrical Supply Cord (cm) Po Plug type Ne Depth with open door 90 degree (mm) - Height of the product Seps Width of the product Seps Usable volume (of cavity) To Net weight (kg) Seps Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity	Main colour of product	Inox
Type of control settings Brončana Ne Which kind of hobs can be controlled? Automatic programmes Ne Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product S95 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Niche depth No Net weight (kg) 29.95 Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity 1	Construction type	Ugradbeni
Brončana Ne Which kind of hobs can be controlled? - Automatic programmes Ne Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Type of control	Mechanical
Which kind of hobs can be controlled? Automatic programmes Ne Current (A) 13 Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 595 Depth of the product 564 Minimum niche height 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity 1	Type of control settings	-
Automatic programmes Current (A) 13 Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Niche depth Ne Ne Depth of the product 595 Depth of the product 595 Depth of the product 564 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity 1	Brončana	Ne
Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Which kind of hobs can be controlled?	-
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Automatic programmes	Ne
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 90 Plug type Ne Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Current (A)	13
Length of Electrical Supply Cord (cm) Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity 1	Voltage (V)	220-240
Plug type Ne Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Frequency (Hz)	50/60
Depth with open door 90 degree (mm) Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) Integrated Cleaning system Hydrolytic Grids of the cavity 1	Length of Electrical Supply Cord (cm)	90
Height of the product 595 Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Plug type	Ne
Width of the product 595 Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Depth with open door 90 degree (mm)	-
Depth of the product 564 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Height of the product	595
Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Depth of the product	564
Niche depth 0 Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Minimum niche height	0
Net weight (kg) 29.95 Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Minimum niche width	0
Usable volume (of cavity) 65 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Niche depth	0
Integrated Cleaning system Hydrolytic Grids of the cavity 1	Net weight (kg)	29.95
Grids of the cavity 1	Usable volume (of cavity)	65
,	Integrated Cleaning system	Hydrolytic
Trays 2	Grids of the cavity	1
	Trays	2

TECHNICAL FEATURES	
Timer	-
Time control	Mechanical
Time-setting options	Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Grids
Probe of the cavity	Ne

ENERGY LABEL		
Energy input	Electric	
Type of energy of the cavity	Electrică	
Energy efficiency class - NEW (2010/30/EU)	A	
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.87	
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.78	