

## WOI78HT1SSGA

## 12NC/Fx: 859991686440

## GTIN (EAN) code: 8003437836947

DIMENSION	MEAS	MEASUR	
OVERALL CABINET			
AIN Height of the wall cabinet niche, including all required space for installation or ventilation	n 0	mm	
AIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm	
AIN Height of the base cabinet niche, including all required space for installation or ventilation	on 595	mn	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	n 0	mn	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	n 585	mn	
MAX Height of the base cabinet niche, including all required space for installation or ventilati	on 596	mn	
AIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn	
AIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mn	
AIN Width of the base cabinet niche, including all required space for installation or ventilation	n 560	mn	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	n 0	mn	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mn	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	n 568	mn	
AIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mr	
AIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mr	
AIN Depth of the base cabinet niche, including all required space for installation or ventilatio	n 550	mr	
Space in front, which is required to install bottom trim	10	mr	
ndicates whether a ventilation opening is needed or not. Default is "N"	Yes		
NALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (wall cabinet)	Rear		
Ainimum space or inbound ventilation (wall cabinet)	0	mr	
Ainimum area for inbound ventilation cavity (wall cabinet)	0	cm	
NALL CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (wall cabinet)	Rear		
Animum space or outbound ventilation (wall cabinet)	0	mr	
Animum area for outbound ventilation cavity (wall cabinet)	0	cm	
TALL CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (tall cabinet)	Rear		
Animum space for inbound ventilation (tall cabinet)	30	mr	
Animum area for inbound ventilation cavity (tall cabinet)	150	cm	
TALL CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (tall cabinet)	Rear		
Animum space for outbound ventilation (tall cabinet)	0	mr	
Animum area for outbound ventilation cavity (tall cabinet)	150	cm	
BASE CABINET (vent-shaft incoming)			
ndicates the position of the freespace for the inbound airflow (base cabinet)	Rear		
Vinimum space for inbound ventilation (base cabinet)	30	mr	
Minimum area for inbound ventilation cavity (base cabinet)	150	cm	
BASE CABINET (vent-shaft outgoing)			
ndicates the position of the freespace for the outbound airflow (base cabinet)	Rear		
Ainimum space for outbound ventilation (base cabinet)	0	mr	
		1000	

DIMENSION		EASURE	
APPLIANCE			
Height of the front	597	mm	
Width of the front	595	mm	
Depth of the front	20	mm	
Maximum depth all protruding elements, e.g. handles, controls	41	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	41	mm	
Projection of front in relation to housing of appliance	18	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	7	mm	
When product panel is missing, set to 0	97	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	462	mm	
Height from bearing area of appliances and lower handle	465	mm	
Frontal handle thickness	41	mn	
Frontal handle width	532	mn	
MIN Height of the product body	572	mn	
MAX Height of the product body	572	mn	
Width of the product body	546	mn	
Depth of the product body	543	mn	
Full depth of product excluding protruding interface elements	564	mn	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Appliance Flap door			
Projection of the opened flap in relation to bearing area	0	mn	
Maximum angle when flap door is opened totally	89	mm	
Appliance Side swing door			
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mn	
Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Maximum angle when door is opened totally	0	mn	
Appliance other			
Depth from front end of the niche to the front end of the freespace of the retrace	345	mn	
Height from niche to bottom end of freespace for the retrace	537	mn	