



| DIMENSION  | MEASURE      |    | DIMENSION   | MEASURE           |                 |
|--|--------------|----|---|-------------------|-----------------|
| <b>APPLIANCE</b>   |              |    | Indicates whether a protection tray against heat or contact is needed with oven. Default is "N"                     | No                |                 |
| Product width  | 590          | mm | Indicates whether a ventilation opening in the back side of cabinet is needed or not with oven. Default is "Y"      | Yes               |                 |
| Product depth  | 510          | mm | Indicates the position of the opening in the back side of the cabinet with oven                                     | Top               |                 |
| Radius of product corner   | 10           | mm | MIN Width of rear opening required with oven  | 550               | mm              |
| Product height (MAX protrusion from the worktop)                           | 4            | mm | MIN Depth of rear opening required with oven.   | 45                | mm              |
| Underneath the bearing area of the appliance                               | 50           | mm | MIN AREA of rear opening required with oven   | 247.5             | cm <sup>2</sup> |
| Distance between cut out and top frontal projection                        | 15           | mm | MIN distance from cabinet to rear wall, with oven   | 20                | mm              |
| Distance between cut out and top lateral projection                        | 15           | mm | Indicates whether a ventilation opening in the top front side of cabinet is needed or not with oven. Default is "N" | No                |                 |
| Plateau thickness  | 4            | mm | MIN Frontal gap required, with oven (2)   | 0                 | mm              |
| Gas outlet positioning   | N/A          |    | MIN frontal opening area required with oven   | 0                 | cm <sup>2</sup> |
| Gas outlet X positioning   | 0            | mm | <b>WITH CABINET</b>   |                   |                 |
| Gas outlet Y positioning   | 0            | mm | MIN worktop thickness with cabinet  | 12                | mm              |
| Power cable  | With product |    | MAX worktop thickness with cabinet  | 0                 | mm              |
| Power cable positioning  | Rear left    |    | Indicates whether a protection tray against heat or contact is needed. Default is "Y"                               | Yes               |                 |
| <b>CUT OUT</b>   |              |    | MIN distance from bottom line of appliance to protection tray   | 10                | mm              |
| MIN front distance from cut-out to end worktop                             | 0            | mm | Indicates whether a ventilation opening in the tray is needed or not with cabinet                                   | Yes               |                 |
| MIN rear distance from cut out to wall/furniture                           | 35           | mm | Recess dimension X  | 90                | mm              |
| MIN lateral distance from cut out to wall/furniture                        | 100          | mm | Recess dimension Y  | 120               | mm              |
| MIN height from worktop to above furniture                                 | 400          | mm | Positioning dimension X by axis   | 45                | mm              |
| MIN cut out width  | 560          | mm | Distance of the tray from the back panel/wall   | 60                | mm              |
| MAX cut out width  | 562          | mm | Indicates whether a divider is available  | Service accessory |                 |
| MIN cut out depth  | 480          | mm | Indicates whether a ventilation opening in the back side of cabinet is needed or not. Default is "Y"                | Yes               |                 |
| MAX cut out depth  | 492          | mm | Indicates the position of the opening in the back side of the cabinet.  | Top               |                 |
| MIN cut out radius   | 0            | mm | MIN Width of rear opening of the cabinet  | 550               | mm              |
| MAX cut out radius   | 10           | mm | MIN Depth of rear opening of the cabinet  | 45                | mm              |
| <b>FLUSH INSTALLATION</b>  |              |    | MIN AREA of rear opening of the cabinet   | 247.5             | cm <sup>2</sup> |
| Indicates whether a flush installation is possible. Default is "N"         | Yes          |    | MIN distance from cabinet to rear wall  | 20                | mm              |
| MIN Milling rabbet width   | 593          | mm | Indicates whether a ventilation opening in the top front side of cabinet is needed or not. Default is "N"           | No                |                 |
| MAX Milling rabbet width   | 595          | mm | MIN Frontal gap of the cabinet  | 0                 | mm              |
| MIN Milling rabbet depth   | 513          | mm | MIN frontal opening area of the cabinet   | 0                 | cm <sup>2</sup> |
| MAX Milling rabbet depth   | 515          | mm | <b>INSTALLATION SPACE</b>   |                   |                 |
| Milling rabbet thickness   | 6            | mm | Depth of immersion underneath the appliance   | 0                 | mm              |
| Radius milling rabbet  | 11.5         | mm | Width protruding area below bottom box  | 0                 | mm              |
| Flush installation KIT (2)   | Service KIT  |    | Depth protruding area below bottom box  | 0                 | mm              |
| Indicates the minum worktop thickness with standard installation for gas   | 0            | mm | Protruding area: X positioning  | 0                 | mm              |
| Indicates the maximum worktop thickness with standard installation for gas | 0            | mm | Protruding area: Y positioning  | 0                 | mm              |
| Indicates the minum worktop thickness with flush installation for gas      | 0            | mm | <b>ACCESSORIES FOR INSTALLATION</b>   |                   |                 |
| Indicates the maximum worktop thickness with flush installation for gas    | 0            | mm | Gasket  | Pre assembled     |                 |
| <b>WITH OVEN</b>   |              |    |   |                   |                 |
| Indicates whether the cooktop can be installed above oven. Default is "Y"  | Yes          |    |   |                   |                 |
| MIN worktop thickness with oven  | 28           | mm |   |                   |                 |
| MAX worktop thickness with oven  | 0            | mm |   |                   |                 |

**DIMENSION****MEASURE**

|   |                 |    |
|---|-----------------|----|
| Clips   | Separate<br>KIT |    |
| Injector KIT                                    | N/A             |    |
| Elbow KIT                                       | N/A             |    |
| <b>COOKTOP HOOD INSTALLATION ONLY FOR GAS</b>   |                 |    |
| MIN distance from cooktop to above furniture    | 0               | mm |
| MIN distance between cabinets above the cooktop | 0               | mm |
| MAX distance between cabinets above the cooktop | 0               | mm |