

## 12NC/Fx: F167209

GTIN (EAN) code: 8050147672099

DIMENSION MEASURE		
OVERALL CABINET		
01. Height MIN of the base cabinet Niche, including all required space for installation or ventilation (HMIN_B)	820	mn
02. Height MAX of the base cabinet Niche, including all required space for installation or ventilation (HMAN_B)	900	mn
03. Width MIN of the base cabinet Niche, including all required space for installation or ventilation (WMIN_B)	450	mr
04.Width MAX of the base cabinet Niche, including all required space for installation or ventilation (WMAN_B)	458	mr
05. Depth of the base cabinet Niche, including all required space for installation or ventilation (DN_B)	560	mr
06. Indicates whether a ventilation opening is needed or not. Default is "N"	No	
07. appliance can be used as base for other appliances from the same manufacturer. Default is "N"	No	
Built In - Floor Standing		
08. Height MIN Decorative Front (HMIF)	653	mr
09. Height MAX Decorative Front (HMAF)	720	mr
10. Width MIN Decorative Front (WMIF)	445	mr
11. Weight MAX of the decorative bottom front panel of the Kitchen manufacturer (WEMAF)	7.5	kg
12. Weight MIN of the decorative front panel of the Kitchen manufacturer (WEMIF)	2	kg
13. Thickness MAX of decorative front panel of the kitchen manufacturers (TMAF)	50	m
14. Minimum height of gap between front and front underneath, with MAX thickness of front (HMIFG)	3	m
APPLIANCE		
Overall Appliance		
01. Height MIN Product (HMIP)	820	mı
02. Height MAX product (HMAP)	900	mı
03. Width product (WP)	448	m
04. Depth product without front (DP)	555	m
05. Depth product (D)	0	m
06. Depth MIN of plinth return front (DMIPRF)	87	m
07. Depth MAX of plinth return front (DMAPRF)	87	m
08. Height MIN Plinth return. Dimension is taken by minimum appliance height (HMIMIPR)	93	m
09. Height MAX Plinth return. Dimension is taken at minimum appliance height (HMIMAPR)	160	m
10. Height MIN Plinth return. Dimension is taken by maximum appliance height (HMAMIPR)	173	m
11. Height MAX Plinth return. Dimension is taken at maximum appliance height (HMAMAPR)	240	m
Built In - Floor Standing		
12. Height MIN Product Panel. When product panel is missing, set to 0 (HMIPP)	0	m
13. Height MAX Product Panel. When product panel is missing, set to 0 (HMAPP)	0	m
14. Space in front, which is required to guarantee full operability. The most protruding part gives this dimension (RSF)	590	m
15. Type of preparation to fix the cover door	Drilling template standard	
Retrace back socie		
16. Depth of the socle retrace at the rear side (DBSR)	48	m
17. Height of the socle retrace at the rear side. This dimension is taken at minimum appliance height (HBSR)	120	mı
TEMPLATE NAME		
00. Name of the template to be used	DISH_FULLDOOR450	СМ