

## PRODUCT FICHE HOOD

<b>Trademark</b>	HOTPOINT
<b>Model identifier</b>	PHPN9.5FLMX/1
<b>Annual Energy Consumption</b>	68,5 kWh/a
<b>Energy Efficiency Class</b>	D
<b>Fluid Dynamic Efficiency</b>	11,9
<b>Fluid Dynamic Efficiency class</b>	E
<b>Lighting efficiency in lux/Watt</b>	76,1 lux/W
<b>Lighting efficiency class</b>	A
<b>Grease filtering efficiency</b>	75,1 %
<b>Grease filtering efficiency class</b>	C
<b>Minimum air flow</b>	290 m <sup>3</sup> /h
<b>Maximum Air flow</b>	435 m <sup>3</sup> /h
<b>Air flow boost</b>	0 m <sup>3</sup> /h
<b>A-weighted sound power at min. speed</b>	56 dB(A)
<b>A-weighted sound power at max. speed</b>	65 dB(A)
<b>A-weighted sound power boost</b>	0 dB(A)
<b>Power consumption in off-mode</b>	0,49 W
<b>Power consumption in standby mode</b>	0,00 W
<b>Time increase factor (f)</b>	1,6
<b>Energy Efficiency Index (EEI<sub>hood</sub>)</b>	86,6
<b>Measured air flow rate at best efficiency point (Q<sub>BEP</sub>)</b>	250,0 m <sup>3</sup> /h
<b>Measured air pressure at best efficiency point (P<sub>BEP</sub>)</b>	190 Pa
<b>Measured electric power input at best efficiency point (W<sub>BEP</sub>)</b>	111,0 W
<b>Nominal power of the lighting system (W<sub>L</sub>)</b>	5,0 W
<b>Average illumination of the lighting system on the cooking surface (E<sub>middle</sub>)</b>	381 lux