
## **AKZM 6560/IXL**

12NC: 852565601100

GTIN (EAN) code: 8003437827747







Product group Oven  Commercial code AKZM 6560/IXL  Main colour of product Inox  Construction type Built-in  Type of control Electronic  Type of control settings - Are any hobs controls integrated? No  Which kind of hobs can be controlled? - Automatic programmes  Current (A) 16  Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type No  Depth with open door 90 degree (mm) - Pleight of the product 595  Width of the product 595  Width of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 1  Integrated Cleaning system Catalytic partial Grids of the cavity 1  Trays 3	MAIN FEATURES	
Main colour of productInoxConstruction typeBuilt-inType of controlElectronicType of control settings-Are any hobs controls integrated?NoWhich kind of hobs can be controlled?-Automatic programmesYesCurrent (A)16Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)90Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Niche depth0Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemCatalytic partialGrids of the cavity1	Product group	Oven
Construction type Type of control Type of control Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? Automatic programmes Ves Current (A) Voltage (V) Frequency (Hz) Length of Electrical Supply Cord (cm) Plug type No Depth with open door 90 degree (mm) - Height of the product Sp5 Width of the product Sp5 Depth of the product Minimum niche height O Note depth No Net weight (kg) Usable volume (of cavity) Table 11 Integrated Cleaning system Catalytic partial Grids of the cavity  1	Commercial code	AKZM 6560/IXL
Type of control Type of control settings	Main colour of product	Inox
Type of control settings  Are any hobs controls integrated?  Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Depth with open door 90 degree (mm)  Height of the product  Depth of the product  Depth of the product  Depth of the product  Minimum niche height  No  Nothe depth  No  Net weight (kg)  No  Sassan  Catalytic partial  Grids of the cavity  1	Construction type	Built-in
Are any hobs controls integrated?  Which kind of hobs can be controlled?  Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Depth with open door 90 degree (mm)  Height of the product  Depth of the product  Depth of the product  Depth of the product  Minimum niche height  No  Niche depth  No  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  No  No  No  Catalytic partial  Grids of the cavity  1	Type of control	Electronic
Which kind of hobs can be controlled?  Automatic programmes Yes  Current (A) 16  Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) Plug type No  Depth with open door 90 degree (mm) - Height of the product 595  Width of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) Integrated Cleaning system Catalytic partial Grids of the cavity 1	Type of control settings	-
Automatic programmes  Current (A)  Voltage (V)  Frequency (Hz)  Length of Electrical Supply Cord (cm)  Plug type  No  Depth with open door 90 degree (mm)  Height of the product  S95  Width of the product  595  Width of the product  595  Depth of the product  596  Minimum niche height  0  Niche depth  No  Net weight (kg)  35.5  Usable volume (of cavity)  Integrated Cleaning system  Grids of the cavity  1	Are any hobs controls integrated?	No
Current (A) 16  Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type No  Depth with open door 90 degree (mm) -  Height of the product 595  Width of the product 595  Depth of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 73  Integrated Cleaning system Catalytic partial	Which kind of hobs can be controlled?	-
Voltage (V) 220-240  Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type No  Depth with open door 90 degree (mm) -  Height of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 73  Integrated Cleaning system Catalytic partial  Grids of the cavity 1	Automatic programmes	Yes
Frequency (Hz) 50/60  Length of Electrical Supply Cord (cm) 90  Plug type No  Depth with open door 90 degree (mm) -  Height of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 73  Integrated Cleaning system Catalytic partial  Grids of the cavity 1	Current (A)	16
Length of Electrical Supply Cord (cm)  Plug type  No  Depth with open door 90 degree (mm)  Height of the product  595  Width of the product  595  Depth of the product  564  Minimum niche height  0  Minimum niche width  Niche depth  Net weight (kg)  Usable volume (of cavity)  Integrated Cleaning system  Grids of the cavity  1	Voltage (V)	220-240
Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product564Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemCatalytic partialGrids of the cavity1	Frequency (Hz)	50/60
Depth with open door 90 degree (mm)  Height of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) Talentary Catalytic partial Grids of the cavity 1	Length of Electrical Supply Cord (cm)	90
Height of the product 595  Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 73  Integrated Cleaning system Catalytic partial  Grids of the cavity 1	Plug type	No
Width of the product 595  Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 73  Integrated Cleaning system Catalytic partial  Grids of the cavity 1	Depth with open door 90 degree (mm)	-
Depth of the product 564  Minimum niche height 0  Minimum niche width 0  Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 73  Integrated Cleaning system Catalytic partial  Grids of the cavity 1	Height of the product	595
Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemCatalytic partialGrids of the cavity1	Width of the product	595
Minimum niche width0Niche depth0Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemCatalytic partialGrids of the cavity1	Depth of the product	564
Niche depth 0  Net weight (kg) 35.5  Usable volume (of cavity) 73  Integrated Cleaning system Catalytic partial  Grids of the cavity 1	Minimum niche height	0
Net weight (kg)35.5Usable volume (of cavity)73Integrated Cleaning systemCatalytic partialGrids of the cavity1	Minimum niche width	0
Usable volume (of cavity) 73 Integrated Cleaning system Catalytic partial Grids of the cavity 1	Niche depth	0
Integrated Cleaning system     Catalytic partial       Grids of the cavity     1	Net weight (kg)	35.5
Grids of the cavity 1	Usable volume (of cavity)	73
•	Integrated Cleaning system	Catalytic partial
Trays 3	Grids of the cavity	1
	Trays	3

TECHNICAL FEATURES	
Timer	-
Time control	Electronic
Time-setting options	Start and Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Rear
Oven guides of the cavity	Telescopic
Probe of the cavity	No

PERFORMANCES		
Energy input	Electric	
Type of energy of the cavity	Electricity	
Energy efficiency class	A+	
Energy consumption conventional (kWh)	0.89	
Energy consumption forced air convection (kWh)	0.69	