

WMD54MB

12NC/Fx: 859991682020

GTIN (EAN) code: 8003437397257

DIMENSION	MEAS	SUR
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	380	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	380	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	382	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	382	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm
Space in front, which is required to install bottom trim	7	mn
ndicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mn
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm
WALL CABINET (vent-shaft outgoing)		
ndicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm
TALL CABINET (vent-shaft incoming)		
indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Vinimum space for inbound ventilation (tall cabinet)	0	mm
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm
BASE CABINET (vent-shaft incoming)		
ndicates the position of the freespace for the inbound airflow (base cabinet)	-	
Vinimum space for inbound ventilation (base cabinet)	0	mn
Vinimum area for inbound ventilation cavity (base cabinet)	0	cm
BASE CABINET (vent-shaft outgoing)	-	51
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mn
Minimum area for outbound ventilation cavity (base cabinet)	0	cm

Depth of the front20mmMaximum depth all protruding elements, e.g. handles, controls41mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front in relation to bousing of appliance12mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension290mmHeight from bearing area of appliances and lower handle269mmFrontal handle thickness373mmMIN Height of the product body373mmMIN Height of the product body373mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmDiameter maximum air outlet0mmDiameter raximum air outlet0mmMaximum angle when flap in relation to bearing area0mmMaximum angle when flap in orelation to bearing area5mmMaximum angle when flap in orelation to bearing area5mmMurineter maximum air outlet0mmmmMaximum height from bottom line hood tot pilne air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0	DIMENSION ME		ASURE	
Width of the front595mmDepth of the front20mmMaximum depth all protruding elements, e.g. handles, controls41mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees12mmProjection of front in relation to busing of appliance12mmProjection of front in relation to busing area of the appliance. Taken at minimum height of appliance, if height is adjustable80mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension20mmHeight from bearing area of appliances and lower handle269mmFrontal handle thickness41mmFrontal handle to the product body373mmMX Height of the product body373mmMUH height fort he product body373mmMuth dight of the product body448mmDepth of product excluding protruding interface elements0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmmmDiameter maximum air outlet0mmDiameter maximum air outlet<	APPLIANCE			
Depth of the front20mmMaximum depth all protruding elements, e.g. handles, controls41mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degreesmmProjection of front in relation to bousing of applianceTaken at minimum height of appliance, if height is adjustablemmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension200mmFrontal handle thickness41mmFrontal handle thickness733mmMXX Height of the product body373mmMXI Height of the product body373mmWidth of the product body373mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter minimum air outlet0mmDiameter minimum air outlet0mmAppliance flap doormmmmAppliance flap doormmAppliance flap door is opened totallyAt he side where the hinge is fixedAppliance flap doormmApp	Height of the front	385	mm	
Maximum depth all protruding elements, e.g. handles, controls41mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front in relation to housing of appliance12mmProjection of front in relation to boaring area of the appliance. Taken at minimum height of appliance, if height is adjustable00mmWhen product panel is missing, set to 0800mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension290mmHeight from bearing area of appliances and lower handle269mmFrontal handle thickness410mmFrontal handle thickness373mmMIN Height of the product body373mmMith of the product body373mmWidth of the product body448mmFull depth of product body448mmMinimum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter Flap doorNoApplianceProjection of the opened flap in relation to bearing area0mmAppliance area use as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap doorNoNoNoAppliance and use as base for other appliances from the same manufacturer. Default is "No"NoAppliance and use as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door <t< td=""><td>Width of the front</td><td>595</td><td>mm</td></t<>	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front in relation to housing of appliance0mmProjection of front in relation to busing of appliance12mmappliance, if height is adjustable80mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension290mmHeight from bearing area of appliances and lower handle269mmFrontal handle thickness41mmMIN Height of the product body373mmMX Height of the product body373mmMX Height of the product body373mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmAppliance flap door0mmAppliance flap door0mmAppliance flap door0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmAppliance flap door0mmAppliance flap door0mmAppliance flap door0mmAppliance flap door0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmAppliance flap door0mmAppliance flap door0mm<	Depth of the front	20	mm	
neighbour front more than 90 degrees12mmProjection of front in relation to housing of appliance12mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable0mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension290mmHeight from bearing area of appliances and lower handle269mmFrontal handle thickness41mmFrontal handle width532mmMAX Height of the product body373mmWidth of the product body373mmWidth of the product body373mmWidth of the product body539mmDepth of product excluding protruding interface elements468mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmProjection of the rear flap in relation to bearing area0mmAppliance Carbe used as base for other appliances from the same manufacturer. Default is "No"NoProjection of the opened flap in relation to bearing area0mmAppliance Carbe used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Side swing door1mmLateral projection of front incl. controls whe	Maximum depth all protruding elements, e.g. handles, controls	41	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable mm splaince, if height is adjustable mms space in front, which is required to guarantee full operability. The most protruding part gives this dimension mm frontal handle thickness 200 mm front handle thickness 41 mm Frontal handle thickness 41 mm MAX Height of the product body 373 mm MAX Height of the product body 373 mm MiN Height of the product body 373 mm MiN Height of the product body 373 mm full depth of product excluding protruding interface elements 468 mm Minimum height from bottom line hood to top line air outlet 0 mm Jameter maximum air outlet 0 mm Jameter maximum air outlet 0 mm Projection of the rear flap in relation to bearing area 0 mm Maximum angle when flap hoor is opened totally Appliance Side swing door 1 measure splace for the trace of the respace of the retrace 0 mm Maximum angle when door is opened totally. At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the enter acce 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opened totally At the side where the hinge is fixed 0 mm Maximum angle when door is opene		0	mm	
appliance, if height is adjustableandadjustable <th< td=""><td>Projection of front in relation to housing of appliance</td><td>12</td><td>mm</td></th<>	Projection of front in relation to housing of appliance	12	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension290mmHeight from bearing area of appliances and lower handle269mmFrontal handle thickness41mmFrontal handle width532mmMIN Height of the product body373mmMAX Height of the product body373mmWidth of the product body539mmDepth of the product body539mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door0mmAppliance Flap door0mmAppliance Side swing door85mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0Appliance other0mmAppliance other0mmMaximum angle when door is opened totally0mmAppliance other0mmAppliance other0mmAppliance other0mmAppliance Other0mmAppliance flap door is opened totally0mmAppliance flap door is opened totally0mmAppliance Side swing door0mmLateral projection of opened front at the side where t	, , , , , , , , , , , , , , , , , , , ,	0	mm	
dimension269mmHeight from bearing area of appliances and lower handle269mmFrontal handle thickness41mmFrontal handle width532mmMIN Height of the product body373mmMAX Height of the product body373mmWidth of the product body448mmFull depth of product body448mmFull depth of product excluding protruding interface elements468mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door5mmProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally. At the side where the hinge is fixed0mmAppliance Side swing door0mmmmLateral projection of opened front at the side where the hinge is fixed0mmAppliance Other0mmmmAppliance Side swing door0mmLateral projection of opened totally0mmAppliance Side swing door0mmLateral projection of opened totally0mmAppliance Side swing door0mmLateral projection of opened totally0mm <td>When product panel is missing, set to 0</td> <td>80</td> <td>mm</td>	When product panel is missing, set to 0	80	mm	
Frontal handle thickness41mmFrontal handle width532mmMIN Height of the product body373mmMAX Height of the product body373mmWidth of the product body539mmDepth of the product body448mmFull depth of product excluding protruding interface elements468mmMaximum height from bottom line hood to top line air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Side swing door5mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is0Lateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm		290	mm	
Frontal handle width532mmMIN Height of the product body373mmMAX Height of the product body373mmWidth of the product body539mmDepth of the product body448mmFull depth of product excluding protruding interface elements468mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door0mmAppliance Side swing door5mmLateral projection of opened flop in relation to bearing area0mmAppliance Side swing door0mmAppliance Side swing door0mmLateral projection of opened flop in relation to bearing area0mmAppliance Side swing door0mmAppliance Side swing door0mmDatateral projection of popened totally0mmAppliance Side swing door0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmmmDepth from front end of the niche to the front end of the freespace of the retrace0mmAppliance Side swing door0mmmmDiateral projection of opened fr	Height from bearing area of appliances and lower handle	269	mm	
MIN Height of the product body373mmMAX Height of the product body373mmWidth of the product body539mmDepth of the product body448mmFull depth of product excluding protruding interface elements468mmMinimum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door0mmProjection of the opened flap in relation to bearing area5mmAppliance Side swing door5mmAppliance Side swing door0mmLateral projection of opened front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmAppliance other0mmAppliance other0mmDaximum angle when door is opened totally0mmAppliance other0mmDaximum angle when door is opened totally0mmAppliance other0mmDaximum angle when door is opened totally0mmDaximum angle when door is op	Frontal handle thickness	41	mm	
MAX Height of the product body373mmWidth of the product body539mmDepth of the product body448mmFull depth of product excluding protruding interface elements468mmMinimum height from bottom line hood to top line air outlet0mmDameter minimum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Flap door11Projection of the opened flap in relation to bearing area5mmAppliance Side swing door11Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mm <td>Frontal handle width</td> <td>532</td> <td>mm</td>	Frontal handle width	532	mm	
Width of the product body539mmDepth of the product body448mmFull depth of product excluding protruding interface elements468mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmDiameter maximum air outlet0mmProjection of the rear flap in relation to bearing area0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door11Projection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing door11mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDiatered projection of the niche to the front end of the freespace of the retrace0mmDiatered projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDiatered projection of the niche to the front end of the freespace of the retrace0 <td< td=""><td>MIN Height of the product body</td><td>373</td><td>mm</td></td<>	MIN Height of the product body	373	mm	
Depth of the product body448mmFull depth of product excluding protruding interface elements468mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"No1Appliance Flap door7mmProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally. At the side where the hinge is mounted0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmAppliance other0mmmmDatateral projection of front incl. controls when door is opened totally. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmmmAppliance other0mmmmDatateral projection of front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiater other0mmM	MAX Height of the product body	373	mm	
Full depth of product excluding protruding interface elements468mmMinimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"No1Projection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Width of the product body	539	mm	
Minimum height from bottom line hood to top line air outlet0mmMaximum height from bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmAppliance Can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door0mmProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDateral projection of front incl. controls when the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDateral projection of front incl. controls when the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Depth of the product body	448	mm	
Maximum alge throm bottom line hood to top line air outlet0mmDiameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door5mmMaximum angle when flap door is opened totally85mmAppliance Side swing door5mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDiateral projection of popened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmMaximum angle when door is ope	Full depth of product excluding protruding interface elements	468	mm	
Diameter minimum air outlet0mmDiameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoAppliance Flap door7NoProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing door7mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDiateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Minimum height from bottom line hood to top line air outlet	0	mm	
Diameter maximum air outlet0mmIndicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NommAppliance Flap doorNoMommProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing doormmmmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmMaximum angle when door is opened totally0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Maximum height from bottom line hood to top line air outlet	0	mm	
Indicates measure between center of air outlet hole and rear wall0mmProjection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoMoAppliance Flap doorNoMoProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorNoMoLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Diameter minimum air outlet	0	mm	
Projection of the rear flap in relation to bearing area0mmHeight tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoMoAppliance Flap doorNoMoMoProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing doormmmmLateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Diameter maximum air outlet	0	mm	
Height tube connection for air outlet0mmAppliance can be used as base for other appliances from the same manufacturer. Default is "No"NoImmAppliance Flap doorImmImmImmProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing doorImmImmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Indicates measure between center of air outlet hole and rear wall	0	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"NoApplianceAppliance Flap door5mmProjection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing door0mmLateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Projection of the rear flap in relation to bearing area	0	mm	
Appliance Flap doorImage: Second	Height tube connection for air outlet	0	mm	
Projection of the opened flap in relation to bearing area5mmMaximum angle when flap door is opened totally85mmAppliance Side swing door11Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Maximum angle when flap door is opened totally 85 mm Appliance Side swing door 1 1 Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted 0 mm Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Appliance Flap door			
Appliance Side swing door Image: Side swing door <t< td=""><td>Projection of the opened flap in relation to bearing area</td><td>5</td><td>mm</td></t<>	Projection of the opened flap in relation to bearing area	5	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted0mmLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Maximum angle when flap door is opened totally	85	mm	
mountedmountedmountedLateral projection of opened front at the side where the hinge is fixed0mmMaximum angle when door is opened totally0mmAppliance other0mmDepth from front end of the niche to the front end of the freespace of the retrace0mm	Appliance Side swing door			
Maximum angle when door is opened totally 0 mm Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mm	
Appliance other 0 mm Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 0 mm	Maximum angle when door is opened totally	0	mm	
	Appliance other			
Height from niche to bottom end of freespace for the retrace 0 mm	Depth from front end of the niche to the front end of the freespace of the retrace	0	mm	
	Height from niche to bottom end of freespace for the retrace	0	mm	