
OMK58HR0X

12NC: 859991659960

GTIN (EAN) code: 8003437939242







- SmartClean
- Energy class A+
- Cavity 71 L
- Cook3
- Forced Air Fan Cooking
- Grill
- Easy Clean Enamel Interior
- Turbo grill function
- Maxi cooking
- Pizza/Bread function
- Eco Forced Air
- Rising
- Special functions
- Tilting Grill for easy cleaning
- Conventional Cooking
- Door Glasses Number: 2
- Timer

Whirlpool built in electric oven: inox color, self cleaning - OMK58HR0X

This Whirlpool built in Oven features: advanced electric technology allowing you to cook dishes saving energy. Innovative Cook3 function, that allows you to cook up to three separate dishes at the same time, without the risk of aromas mixing.



Cook3

No aroma mixing. With the innovative Cook3 function, you can cook up to three separate dishes at the same time, without the risk of aromas mixing.



Multifunction 8

Multiple cooking methods. The Multifunction 8 feature offers flexible cooking options, to ensure perfect results, whatever the recipe.



EasyClean Door

Internal glass of the door can be easily removed for cleaning.



Electronic control

Electronic temperature control.



Pizza

Get the best results and a crispy base for your pizzas.



Standard cavity

This Whirlpool Oven features a standard-size cavity.



Energy class A+

Greater energy efficiency. With its A+ energy rating, this Whirlpool appliance will allow you to enjoy both ideal performance and excellent energy consumption.



Auto Pastry

Easily bake your pastry dishes. Once the function is selected by turning the knob, the time and temperature are set automatically. The oven stops after 45 minutes.



Maxi Cooking

Perfectly cook big portions of food. Ideal for big roasts.



Auto Bread

Bake different types of breads, effortlessly. Once the function is selected by turning the knob, the time and temperature are set automatically. The oven stops after 1 hour.

OMK58HR0X

12NC: 859991659960

GTIN (EAN) code: 8003437939242



SENSING THE DIFFERENCE

Product group Oven Commercial code OMKS8HROX Main colour of product Inox Construction type Built-in Type of control Electronic Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? Yes Automatic programmes Yes Current (A) 13 Voltage (V) 200-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Width of the product 595 Width of the product 595 Width of the product 595 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Niche degth 0 Niche degth 0 <th colspan="2">MAIN FEATURES</th>	MAIN FEATURES	
Main colour of product Inox Construction type Built-in Type of control Electronic Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Width of the product 595 Depth with open door 90 degree (mm) 0 Height of the product 595 Width of the product 595 Width of the product 0 Minimum niche width 0 Niche depth 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydro	Product group	Oven
Construction typeBuilt-inType of controlElectronicType of control settings-Are any hobs controls integrated?NoWhich kind of hobs can be controlled?-Automatic programmesYesCurrent (A)13Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)100Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product height0Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)27.55Usable volume (of cavity)71Integrated Cleaning systemHydrolyticGrids of the cavity1	Commercial code	OMK58HR0X
Type of control Electronic Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 595 Minimum niche height 0 Minimum niche height 0 Miche depth 0 Niche depth 0 Vasble volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Main colour of product	Inox
Type of control settings - Are any hobs controls integrated? No Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Construction type	Built-in
Are any hobs controls integrated?NoWhich kind of hobs can be controlled?-Automatic programmesYesCurrent (A)13Voltage (V)220-240Frequency (Hz)50/60Length of Electrical Supply Cord (cm)100Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Width of the product551Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)27.55Usable volume (of cavity)71Integrated Cleaning systemHydrolyticGrids of the cavity1	Type of control	Electronic
Which kind of hobs can be controlled? - Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Type of control settings	-
Automatic programmes Yes Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Are any hobs controls integrated?	No
Current (A) 13 Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Which kind of hobs can be controlled?	-
Voltage (V) 220-240 Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Automatic programmes	Yes
Frequency (Hz) 50/60 Length of Electrical Supply Cord (cm) 100 Plug type No Depth with open door 90 degree (mm) - Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Current (A)	13
Length of Electrical Supply Cord (cm)100Plug typeNoDepth with open door 90 degree (mm)-Height of the product595Width of the product595Depth of the product551Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)27.55Usable volume (of cavity)71Integrated Cleaning systemHydrolyticGrids of the cavity1	Voltage (V)	220-240
Plug type	Frequency (Hz)	50/60
Depth with open door 90 degree (mm) Height of the product S95 Width of the product S95 Depth of the product S151 Minimum niche height Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Grids of the cavity T1	Length of Electrical Supply Cord (cm)	100
Height of the product 595 Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Plug type	No
Width of the product 595 Depth of the product 551 Minimum niche height 0 Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Depth with open door 90 degree (mm)	-
Depth of the product551Minimum niche height0Minimum niche width0Niche depth0Net weight (kg)27.55Usable volume (of cavity)71Integrated Cleaning systemHydrolyticGrids of the cavity1	Height of the product	595
Minimum niche height Minimum niche width Niche depth Net weight (kg) Usable volume (of cavity) Integrated Cleaning system Grids of the cavity 1 0 27.55 Hydrolytic	Width of the product	595
Minimum niche width 0 Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 1	Depth of the product	551
Niche depth 0 Net weight (kg) 27.55 Usable volume (of cavity) 71 Integrated Cleaning system Hydrolytic Grids of the cavity 11	Minimum niche height	0
Net weight (kg)27.55Usable volume (of cavity)71Integrated Cleaning systemHydrolyticGrids of the cavity1	Minimum niche width	0
Usable volume (of cavity)71Integrated Cleaning systemHydrolyticGrids of the cavity1	Niche depth	0
Integrated Cleaning system Hydrolytic Grids of the cavity 1	Net weight (kg)	27.55
Grids of the cavity 1	Usable volume (of cavity)	71
·	Integrated Cleaning system	Hydrolytic
Trays 2	Grids of the cavity	1
	Trays	2

TECHNICAL FEATURES	
Timer	Yes
Time control	Electronic
Time-setting options	Stop
Safety device	-
Interior light	Yes
Number of interior lights of the cavity	1
Position of interior lights of the cavity	Front left
Oven guides of the cavity	Grids
Probe of the cavity	No

PERFORMANCES	
Energy input	Electric
Type of energy of the cavity	Electricity
Energy efficiency class - NEW (2010/30/EU)	A+
Energy consumption per cycle conventional - NEW (2010/30/EU)	0.89
Energy consumption per cycle forced air convection - NEW (2010/30/EU)	0.69

