

PRODUCT FICHE HOOD

Trademark	INDESIT
Model identifier	UHPM 6.3F CS X/1
Annual Energy Consumption	56,5 kWh/a
Energy Efficiency Class	D
Fluid Dynamic Efficiency	8,9
Fluid Dynamic Efficiency class	E
Lighting efficiency in lux/Watt	16,1 lux/W
Lighting efficiency class	C
Grease filtering efficiency	66,0 %
Grease filtering efficiency class	D
Minimum air flow	165 m ³ /h
Maximum Air flow	395 m ³ /h
Air flow boost	- m ³ /h
A-weighted sound power at min. speed	49 dB(A)
A-weighted sound power at max. speed	68 dB(A)
A-weighted sound power boost	0 dB(A)
Power consumption in off-mode	0,00 W
Power consumption in standby mode	0,00 W
Time increase factor (f)	1,7
Energy Efficiency Index (EEI_{hood})	87,2

Measured air flow rate at best efficiency point (Q_{BEP})	215,0 m ³ /h
Measured air pressure at best efficiency point (P_{BEP})	125 Pa
Measured electric power input at best efficiency point (W_{BEP})	84,0 W
Nominal power of the lighting system (W_L)	6,0 W
Average illumination of the lighting system on the cooking surface (E_{middle})	97 lux