

AKZM 8380/IXL

12NC/Fx: 852583810100

GTIN (EAN) code: 8003437830310

| DIMENSION | MEAS | UR |
|--|-------------|-----------------|
| OVERALL CABINET | | |
| MIN Height of the wall cabinet niche, including all required space for installation or ventilation | 0 | mm |
| MIN Height of the tall cabinet niche, including all required space for installation or ventilation | 583 | mm |
| MIN Height of the base cabinet niche, including all required space for installation or ventilation | 600 | mm |
| MAX Height of the wall cabinet niche, including all required space for installation or ventilation | 0 | mm |
| MAX Height of the tall cabinet niche, including all required space for installation or ventilation | 585 | mm |
| MAX Height of the base cabinet niche, including all required space for installation or ventilation | 601 | mm |
| MIN Width of the wall cabinet niche, including all required space for installation or ventilation | 0 | mm |
| MIN Width of the tall cabinet niche, including all required space for installation or ventilation | 560 | mm |
| MIN Width of the base cabinet niche, including all required space for installation or ventilation | 560 | mm |
| MAX Width of the wall cabinet niche, including all required space for installation or ventilation | 0 | mm |
| MAX Width of the tall cabinet niche, including all required space for installation or ventilation | 568 | mm |
| MAX Width of the base cabinet niche, including all required space for installation or ventilation | 568 | mm |
| MIN Depth of the wall cabinet niche, including all required space for installation or ventilation | 0 | mm |
| MIN Depth of the tall cabinet niche, including all required space for installation or ventilation | 550 | mm |
| MIN Depth of the base cabinet niche, including all required space for installation or ventilation | 550 | mm |
| Space in front, which is required to install bottom trim | 10 | mm |
| Indicates whether a ventilation opening is needed or not. Default is "N" | Yes | |
| WALL CABINET (vent-shaft incoming) | | |
| Indicates the position of the freespace for the inbound airflow (wall cabinet) | Rear | |
| Minimum space or inbound ventilation (wall cabinet) | 0 | mm |
| Minimum area for inbound ventilation cavity (wall cabinet) | 0 | cm ² |
| WALL CABINET (vent-shaft outgoing) | | |
| Indicates the position of the freespace for the outbound airflow (wall cabinet) | Rear | |
| Minimum space or outbound ventilation (wall cabinet) | 0 | mm |
| Minimum area for outbound ventilation cavity (wall cabinet) | 0 | cm ² |
| TALL CABINET (vent-shaft incoming) | | |
| Indicates the position of the freespace for the inbound airflow (tall cabinet) | Rear | |
| Minimum space for inbound ventilation (tall cabinet) | 30 | mm |
| Minimum area for inbound ventilation cavity (tall cabinet) | 150 | cm ² |
| TALL CABINET (vent-shaft outgoing) | | |
| Indicates the position of the freespace for the outbound airflow (tall cabinet) | Rear | |
| Minimum space for outbound ventilation (tall cabinet) | 0 | mm |
| Minimum area for outbound ventilation cavity (tall cabinet) | 150 | cm ² |
| BASE CABINET (vent-shaft incoming) | | |
| Indicates the position of the freespace for the inbound airflow (base cabinet) | Rear | |
| Minimum space for inbound ventilation (base cabinet) | 30 | mm |
| Minimum area for inbound ventilation cavity (base cabinet) | 150 | cm ² |
| BASE CABINET (vent-shaft outgoing) | | |
| Indicates the position of the freespace for the outbound airflow (base cabinet) | Rear | |
| Minimum space for outbound ventilation (base cabinet) | 0 | mm |
| Minimum area for outbound ventilation cavity (base cabinet) | 150 | cm ² |

| DIMENSION | | EASURE | |
|---|-----|--------|--|
| APPLIANCE | | | |
| Height of the front | 595 | mm | |
| Width of the front | 595 | mm | |
| Depth of the front | 20 | mm | |
| Maximum depth all protruding elements, e.g. handles, controls | 0 | mm | |
| Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees | 0 | mm | |
| Projection of front in relation to housing of appliance | 18 | mm | |
| Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable | 6 | mm | |
| When product panel is missing, set to 0 | 95 | mm | |
| Space in front, which is required to guarantee full operability. The most protruding part gives this dimension | 477 | mm | |
| Height from bearing area of appliances and lower handle | 0 | mm | |
| Frontal handle thickness | 0 | mm | |
| Frontal handle width | 0 | mm | |
| MIN Height of the product body | 572 | mm | |
| MAX Height of the product body | 572 | mm | |
| Width of the product body | 546 | mm | |
| Depth of the product body | 543 | mm | |
| Full depth of product excluding protruding interface elements | 564 | mm | |
| Appliance can be used as base for other appliances from the same manufacturer. Default is "No" | No | | |
| Appliance Flap door | | | |
| Projection of the opened flap in relation to bearing area | 0 | mm | |
| Maximum angle when flap door is opened totally | 89 | mm | |
| Appliance Side swing door | | | |
| Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted | 0 | mm | |
| Lateral projection of opened front at the side where the hinge is fixed | 0 | mm | |
| Maximum angle when door is opened totally | 0 | mm | |
| Appliance other | | | |
| Depth from front end of the niche to the front end of the freespace of the retrace | 345 | mm | |
| Height from niche to bottom end of freespace for the retrace | 537 | mm | |