

FA5 844 JH IX A

12NC/Fx: F100156

GTIN (EAN) code: 8050147001561

DIMENSION		MEASURE	
OVERALL CABINET			
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm	
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mm	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mm	
Space in front, which is required to install bottom trim	9	mm	
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes		
WALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear		
Minimum space or inbound ventilation (wall cabinet)	0	mm	
Minimum area for inbound ventilation cavity (wall cabinet)	0	Cm ²	
WALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear		
Minimum space or outbound ventilation (wall cabinet)	0	mm	
Minimum area for outbound ventilation cavity (wall cabinet)	0	Cm ²	
TALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear		
Minimum space for inbound ventilation (tall cabinet)	40	mm	
Minimum area for inbound ventilation cavity (tall cabinet)	150	Cm ²	
TALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear		
Minimum space for outbound ventilation (tall cabinet)	0	mm	
Minimum area for outbound ventilation cavity (tall cabinet)	150	Cm ²	
BASE CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear		
Minimum space for inbound ventilation (base cabinet)	40	mm	
Minimum area for inbound ventilation cavity (base cabinet)	150	cm ²	
BASE CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear		
Minimum space for outbound ventilation (base cabinet)	0	mm	
Minimum area for outbound ventilation cavity (base cabinet)	150	cm ²	

Width of the front 50 Depth of the front 20 Maximum depth all protruding elements, e.g. handles, controls 44 Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees 36	2 mm 3 mm
Width of the front54Depth of the front24Maximum depth all protruding elements, e.g. handles, controls44Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees34	95 mm 0 mm 2 mm 3 mm 0 mm
Depth of the front2Maximum depth all protruding elements, e.g. handles, controls4Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees3) mm 2 mm 3 mm) mm
Maximum depth all protruding elements, e.g. handles, controls 42 Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees 32	2 mm 3 mm 0 mm
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	3 mm) mm
neighbour front more than 90 degrees) mm
Projection of front in relation to housing of appliance 24	mm
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	
When product panel is missing, set to 0 9	7 mm
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 44	30 mm
Height from bearing area of appliances and lower handle 4	25 mm
Frontal handle thickness 3) mm
Frontal handle width 5	19 mm
MIN Height of the product body 5	70 mm
MAX Height of the product body 57	70 mm
Width of the product body 55	58 mm
Depth of the product body 5-	18 mm
Full depth of product excluding protruding interface elements 5	70 mm
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" N	c
Appliance Flap door	
Projection of the opened flap in relation to bearing area 0	mm
Maximum angle when flap door is opened totally 85	9 mm
Appliance Side swing door	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is 0 mounted	mm
Lateral projection of opened front at the side where the hinge is fixed 0	mm
Maximum angle when door is opened totally 0	mm
Appliance other	
Depth from front end of the niche to the front end of the freespace of the retrace 44	28 mm
Height from niche to bottom end of freespace for the retrace 55	25 mm