

## 12NC/Fx: F095733

## GTIN (EAN) code: 5016108957332

DIMENSION	MEAS	URI
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	450	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	453	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	453	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550	mm
Space in front, which is required to install bottom trim	8	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	No	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm <sup>2</sup>
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	
Minimum space for inbound ventilation (tall cabinet)	0	mm
Minimum area for inbound ventilation cavity (tall cabinet)	0	cm <sup>2</sup>
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	0	cm <sup>2</sup>
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	-	
Minimum space for inbound ventilation (base cabinet)	0	mm
Minimum area for inbound ventilation cavity (base cabinet)	0	cm <sup>2</sup>
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	-	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	0	cm <sup>2</sup>

Width of the front 20 mm Maximum depth all protruding elements, e.g. handles, controls 42 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 50 mm Height from bearing area of appliances and lower handle 51 mm Height from bearing area of appliances and lower handle 51 mm HiN Height of the product body 51 mm MAX Height of the product body 52 mm MAX Height of the product body 53 mm Min Height from bottom line hood to top line air outlet 51 mm Maximum height from bottom line hood to top line air outlet 51 mm Maximum height from bottom line hood to top line air outlet 51 mm Minimum height from bottom line hood to top line air outlet 51 mm Minimum height throm bottom line hood to top line air outlet 51 mm Maximum air outlet 51 mm Projection of the rear flap in relation to bearing area 52 mm Projection of the rear flap in relation to bearing area 52 mm Height tube connection for air outlet 52 mm Projection of the opened flap in relation to bearing area 53 mm Projection of the opened flap in relation to bearing area 54 mm Maximum angle when flap door is opened totally 54 the side where the hinge is 55 mm Maximum angle when flap door is opened totally 54 the side where the hinge is 55 mm Maximum angle when door is opened totally 54 the side where the hinge is 50 mm Maximum angle when door is opened totally 55 mm Maximum angle when door is opened totally 55 mm Maximum angle when door is opened totally 56 mm Maximum angle when door is opened totally 57 mm Maximum angle when door is opened totally 58 mm Maximum angle when door is opened totally 58 mm Maximum angle	DIMENSION		EASURE	
Width of the front 20 mm Asximum depth all protruding elements, e.g. handles, controls 42 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle thickness 30 mm AX Height of the product body 447 mm MAX Height of the product body 447 mm Midth of the product body 553 mm Depth of the product body 554 mm Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door Appliance Side swing door Appliance Side swing door Appliance on the note to the front end of the freespace of the retrace  Depth from front end of the nicke to the front end of the freespace of the retrace  Maximum angle when door is opened totally Appliance on the opened front at the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally Appliance on the of the nicke to the front end of the freespace of the retrace  Depth from front end of the nicke to the front end of the freespace of the retrace	APPLIANCE			
Depth of the front  Maximum depth all protruding elements, e.g. handles, controls  Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees  Projection of front in relation to housing of appliance  Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  30 mm  Frontal handle width  MIN Height of the product body  MAX Height of the product body  Width of the product body  Width of the product body  Saba minimum height from bottom line hood to top line air outlet  Maximum height from bottom line hood to top line air outlet  Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Appliance Side swing door  Projection of opened front at the side where the hinge is mounted of the ninge was mounted to the projection of opened front at the side where the hinge is fixed  Appliance on the ninge was a page and a page when door is opened totally. At the side where the hinge is mounted  Depth from front end of the niche to the front end of the freespace of the retrace  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace	Height of the front	455	mm	
Maximum depth all protruding elements, e.g. handles, controls  Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees  Projection of front in relation to housing of appliance  Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  300 mm  Frontal handle width  MIN Height of the product body  MAX Height of the product body  Width of the product body  Moth of the product body  Space in from bottom line hood to top line air outlet  Maximum height from bottom line hood to top line air outlet  Diameter maximum air outlet  Diameter maximum air outlet  Diameter maximum air outlet  Diameter maximum air outlet  Diameter seasure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted to the front end of the front end of the niche to the front end of the freespace of the retrace  140 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  151 mm  152 mm  153 mm  154 mm  155 m	Width of the front	595	mm	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width 519 mm MIN Height of the product body 447 mm MAX Height of the product body Width of the product body 553 mm Full depth of product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter maximum air outlet Diameter flap in relation to bearing area Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Side swing door Lateral projection of front incl. controls when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace  100 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace  100 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace	Depth of the front	20	mm	
neighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension Height from bearing area of appliances and lower handle 302 mm Frontal handle thickness 30 mm Frontal handle width 519 mm MIN Height of the product body 447 mm Width of the product body 553 mm Oberth of the product body 553 mm Full depth of product excluding protruding interface elements Find the product excluding protruding interface elements Minimum height from bottom line hood to top line air outlet Maximum height from bottom line hood to top line air outlet Diameter minimum air outlet Diameter maximum air outlet Diameter between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area Depth of the rear flap in relation to bearing area  Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed  Depth from front end of the niche to the front end of the freespace of the retrace  Depth from front end of the niche to the front end of the freespace of the retrace	Maximum depth all protruding elements, e.g. handles, controls	42	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable  When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  30 mm  Frontal handle width  MIN Height of the product body  447 mm  MIN Height of the product body  553 mm  Depth of the product body  554 mm  Minimum height from bottom line hood to top line air outlet  0 mm  Maximum height from bottom line hood to top line air outlet  0 mm  Diameter maximum air outlet  0 mm  Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Side swing door  Lateral projection of poned front at the side where the hinge is mounted  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace	, , , , , , , , , , , , , , , , , , ,	0	mm	
appliance, if height is adjustable  When product panel is missing, set to 0  Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  Frontal handle thickness  30 mm  Frontal handle width  MIN Height of the product body  MAX Height of the product body  Width of the product body  Depth of the product body  S53 mm  Full depth of product excluding protruding interface elements  Minimum height from bottom line hood to top line air outlet  O mm  Maximum height from bottom line hood to top line air outlet  O mm  Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance Can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of opened front at the side where the hinge is mounted  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace	Projection of front in relation to housing of appliance	10	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension  Height from bearing area of appliances and lower handle  302 mm Frontal handle thickness  Frontal handle width  MIN Height of the product body  MAX Height of the product body  Width of the product body  553 mm Depth of the product excluding protruding interface elements  554 mm Minimum height from bottom line hood to top line air outlet  Maximum height from bottom line hood to top line air outlet  Diameter minimum air outlet  Diameter maximum air outlet  Diameter between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of opened front at the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm  Appliance other	· · · · · · · · · · · · · · · · · · ·	0	mm	
dimension Height from bearing area of appliances and lower handle Frontal handle thickness 30 mm Frontal handle width 519 mm MIN Height of the product body 447 mm Width of the product body 553 mm Depth of the product body 553 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Projection of the rear flap in relation to bearing area 0 mm Height tube connection for air outlet 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door Projection of the opened flap in relation to bearing area 0 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm Appliance other	When product panel is missing, set to 0	95	mm	
Frontal handle thickness 30 mm Frontal handle width 519 mm MIN Height of the product body 447 mm MAX Height of the product body 553 mm Depth of the product body 553 mm Depth of the product body 553 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter maximum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 0 mm Height tube connection for air outlet 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door 1 mm Projection of the opened flap in relation to bearing area 1 mm Maximum angle when flap door is opened totally At the side where the hinge is mounted 1 mm Maximum angle when door is opened totally At the side where the hinge is mounted 1 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Maximum angle when door is opened totally 0 mm Appliance other 1 mm Depth from front end of the niche to the front end of the freespace of the retrace 1 mm  Depth from front end of the niche to the front end of the freespace of the retrace 1 mm		348	mm	
Frontal handle width 519 mm MIN Height of the product body 447 mm MAX Height of the product body 553 mm Width of the product body 553 mm Depth of the product body 553 mm Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Diameter maximum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 0 mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally Appliance Side swing door 1 cateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted 1 mm Maximum angle when door is opened totally 1 mm	Height from bearing area of appliances and lower handle	302	mm	
MIN Height of the product body  MAX Height of the product body  Width of the product body  Depth of the product body  S53 mm Full depth of product excluding protruding interface elements  Full depth of product excluding protruding interface elements  S54 mm Minimum height from bottom line hood to top line air outlet  O mm Maximum height from bottom line hood to top line air outlet  O mm Diameter minimum air outlet  O mm Diameter maximum air outlet  O mm Indicates measure between center of air outlet hole and rear wall  O mm Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  6 mm Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Frontal handle thickness	30	mm	
MAX Height of the product body  Width of the product body  Depth of the product body  Sas mr  Full depth of product excluding protruding interface elements  Minimum height from bottom line hood to top line air outlet  Maximum height from bottom line hood to top line air outlet  Diameter minimum air outlet  Diameter maximum air outlet	Frontal handle width	519	mm	
Width of the product body Depth of the product body Full depth of product excluding protruding interface elements S54 mm Minimum height from bottom line hood to top line air outlet O mm Maximum height from bottom line hood to top line air outlet O mm Diameter minimum air outlet O mm Indicates measure between center of air outlet hole and rear wall Projection of the rear flap in relation to bearing area O mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	MIN Height of the product body	447	mm	
Depth of the product body Full depth of product excluding protruding interface elements 554 mm Minimum height from bottom line hood to top line air outlet 0 mm Maximum height from bottom line hood to top line air outlet 0 mm Diameter minimum air outlet 0 mm Diameter maximum air outlet 0 mm Indicates measure between center of air outlet hole and rear wall 0 mm Projection of the rear flap in relation to bearing area 0 mm Height tube connection for air outlet Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally Appliance Side swing door Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	MAX Height of the product body	447	mm	
Full depth of product excluding protruding interface elements  554 mm Minimum height from bottom line hood to top line air outlet  0 mm Maximum height from bottom line hood to top line air outlet  0 mm Diameter minimum air outlet  0 mm Indicates measure between center of air outlet hole and rear wall  0 mm Projection of the rear flap in relation to bearing area  0 mm Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  6 mm Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Width of the product body	553	mm	
Minimum height from bottom line hood to top line air outlet  Maximum height from bottom line hood to top line air outlet  Diameter minimum air outlet  Diameter maximum air outlet  Diameter maximum air outlet  Diameter maximum air outlet  O mm  Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Depth of the product body	535	mm	
Maximum height from bottom line hood to top line air outlet  Diameter minimum air outlet  Diameter maximum air outlet  Diameter maximum air outlet  Diameter maximum air outlet  O mr  Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mr	Full depth of product excluding protruding interface elements	554	mm	
Diameter minimum air outlet  Diameter maximum air outlet  Diameter maximum air outlet  Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Minimum height from bottom line hood to top line air outlet	0	mm	
Diameter maximum air outlet  Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  0 mm  Appliance other	Maximum height from bottom line hood to top line air outlet	0	mm	
Indicates measure between center of air outlet hole and rear wall  Projection of the rear flap in relation to bearing area  0 mm  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  0 mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Diameter minimum air outlet	0	mm	
Projection of the rear flap in relation to bearing area  Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  O mm  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Diameter maximum air outlet	0	mm	
Height tube connection for air outlet  Appliance can be used as base for other appliances from the same manufacturer. Default is "No"  Appliance Flap door  Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Indicates measure between center of air outlet hole and rear wall	0	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" - Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally 85 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally 0 mm Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Projection of the rear flap in relation to bearing area	0	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area 6 mm Maximum angle when flap door is opened totally 85 mm Appliance Side swing door Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted Lateral projection of opened front at the side where the hinge is fixed 0 mm Maximum angle when door is opened totally Appliance other Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Height tube connection for air outlet	0	mm	
Projection of the opened flap in relation to bearing area  Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  6 mm  M55  mm  M75  M75  M76  M77  M77  M77  M77  M78  M78  M78	Appliance can be used as base for other appliances from the same manufacturer. Default is "No	" -		
Maximum angle when flap door is opened totally  Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  O pepth from front end of the niche to the front end of the freespace of the retrace  140 mm	Appliance Flap door			
Appliance Side swing door  Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Projection of the opened flap in relation to bearing area	6	mm	
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted  Lateral projection of opened front at the side where the hinge is fixed  O mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Maximum angle when flap door is opened totally	85	mm	
mounted  Lateral projection of opened front at the side where the hinge is fixed  0 mm  Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Appliance Side swing door			
Maximum angle when door is opened totally  Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm		s 0	mm	
Appliance other  Depth from front end of the niche to the front end of the freespace of the retrace  140 mm	Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Depth from front end of the niche to the front end of the freespace of the retrace 140 mm	Maximum angle when door is opened totally	0	mm	
	Appliance other			
Height from niche to bottom end of freespace for the retrace 391 mm	Depth from front end of the niche to the front end of the freespace of the retrace	140	mm	
	Height from niche to bottom end of freespace for the retrace	391	mm	