

CM 7945 IX A

12NC/Fx: F100195

GTIN (EAN) code: 8050147001950

DIMENSION		MEASUR	
OVERALL CABINET			
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	450	mm	
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm	
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	452	mm	
MAX Height of the base cabinet niche, including all required space for installation or ventilation	n 0	mn	
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn	
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mn	
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0	mn	
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn	
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mn	
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0	mn	
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mn	
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	545	mn	
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0	mn	
Space in front, which is required to install bottom trim	7	mn	
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes		
WALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear		
Minimum space or inbound ventilation (wall cabinet)	0	mn	
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm	
WALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-		
Minimum space or outbound ventilation (wall cabinet)	0	mn	
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm	
TALL CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear		
Minimum space for inbound ventilation (tall cabinet)	45	mn	
Minimum area for inbound ventilation cavity (tall cabinet)	252	cm	
TALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear		
Minimum space for outbound ventilation (tall cabinet)	45	mn	
Minimum area for outbound ventilation cavity (tall cabinet)	252	cm	
BASE CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (base cabinet)	-		
Minimum space for inbound ventilation (base cabinet)	0	mn	
Minimum area for inbound ventilation cavity (base cabinet)	0	cm	
BASE CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (base cabinet)	-		
Minimum space for outbound ventilation (base cabinet)	0	mm	
Minimum area for outbound ventilation cavity (base cabinet)	0	cm	

APPLIANCE Image: State Sta
Width of the front 595 mm Depth of the front 21 mm Maximum depth all protruding elements, e.g. handles, controls 0 mm Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees 0 mm Projection of front in relation to housing of appliance Taken at minimum height of 2 mm appliance, if height is adjustable 80 mm When product panel is missing, set to 0 80 mm Space in front, which is required to guarantee full operability. The most protruding part gives this dimension 0 mm Frontal handle thickness 0 mm Frontal handle thickness 0 mm MUH Height of the product body 372 mm MUH Height of the product body 376 mm Full depth of product excluding protruding interface elements 398 mm - mm
Depth of the front21mmMaximum depth all protruding elements, e.g. handles, controls0mmLateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees0mmProjection of front in relation to housing of appliance10mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable20mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension0mmFrontal handle thickness0mmFrontal handle thickness0mmMIN Height of the product body372mmMith Height of the product body372mmVidth of the product body376mmFull depth of product excluding protruding interface elements398mm-
Maximum depth all protruding elements, e.g. handles, controls 0 nm Lateral clearance between front edge and most protruding elements which avoid to open a 0 mm Projection of front in relation to housing of appliance 10 mm Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable 2 mm When product panel is missing, set to 0 80 mm Space in front, which is required to guarantee full operability. The most protruding part gives this 207 mm Height from bearing area of appliances and lower handle 0 mm Frontal handle thickness 0 mm MIN Height of the product body 372 mm MAX Height of the product body 372 mm Mult of the product body 372 mm Full depth of product body 372 mm - mm 376 mm - mm - mm - mm - mm - mm - mm Frontal handle thickness - mm Depth of the product body 72
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees0mmProjection of front in relation to housing of appliance10mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable10mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension0mmHeight from bearing area of appliances and lower handle0mmFrontal handle thickness0mmFrontal handle width0mmMIN Height of the product body372mmWith of the product body372mmVidth of the product body376mmFull depth of product excluding protruding interface elements398mm-
neighbour front more than 90 degrees10mmProjection of front in relation to housing of appliance10mmProjection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable2mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension0mmFrontal handle thickness0mmFrontal handle width0mmMIN Height of the product body372mmWidth of the product body372mmWidth of the product body372mmFull depth of product excluding protruding interface elements398mm
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable2mmWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension207mmHeight from bearing area of appliances and lower handle0mmFrontal handle thickness0mmFrontal handle thickness0mmMIN Height of the product body372mmMAX Height of the product body372mmWidth of the product body372mmFull depth of product body376mm
appliance, if height is adjustableandWhen product panel is missing, set to 080mmSpace in front, which is required to guarantee full operability. The most protruding part gives this dimension207mmHeight from bearing area of appliances and lower handle0mmFrontal handle thickness0mmFrontal handle width0mmMIN Height of the product body372mmMAX Height of the product body372mmWidth of the product body528mmPull depth of product body376mmFull depth of product body376mm
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension207mmHeight from bearing area of appliances and lower handle0mmFrontal handle thickness0mmFrontal handle width0mmMIN Height of the product body372mmMAX Height of the product body372mmWidth of the product body528mmDepth of the product body376mmFull depth of product excluding protruding interface elements398mm- </td
dimensionConstraintsConstraintsHeight from bearing area of appliances and lower handle0mmFrontal handle thickness0mmFrontal handle width0mmMIN Height of the product body372mmMAX Height of the product body372mmWidth of the product body528mmDepth of the product body376mmFull depth of product excluding protruding interface elements398mm<
Frontal handle thickness0mmFrontal handle width0mmMIN Height of the product body372mmMAX Height of the product body372mmWidth of the product body528mmDepth of the product body376mmFull depth of product excluding protruding interface elements398mm
Frontal handle width0mmMIN Height of the product body372mmMAX Height of the product body372mmWidth of the product body528mmDepth of the product body376mmFull depth of product excluding protruding interface elements398mm <tr< td=""></tr<>
MIN Height of the product body 372 mm MAX Height of the product body 372 mm Width of the product body 528 mm Depth of the product body 376 mm Full depth of product excluding protruding interface elements 398 mm - - mm
MAX Height of the product body 372 mm Width of the product body 528 mm Depth of the product body 376 mm Full depth of product excluding protruding interface elements 398 mm - -
Width of the product body528mmDepth of the product body376mmFull depth of product excluding protruding interface elements398mm <t< td=""></t<>
Depth of the product body 376 mm Full depth of product excluding protruding interface elements 398 mm - - mm Appliance
Full depth of product excluding protruding interface elements 398 mm - - mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" <
- Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No Hong Appliance same manufacturer. Default is "No" Hong Appliance same manufacture
- - mm
- Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No
- Mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No Home Appliance from the same manufacturer. Default is "No" Home Appliance from the same manufacturer. Default is
- Mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No
- mm - Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No
- mm Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No
Appliance Flap door
Projection of the opened flap in relation to bearing area 0 mm
Maximum angle when flap door is opened totally 0 mm
Appliance Side swing door
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mm mounted
Lateral projection of opened front at the side where the hinge is fixed 0 mm
Maximum angle when door is opened totally 85 mm
Appliance other
Depth from front end of the niche to the front end of the freespace of the retrace 0 mm
Height from niche to bottom end of freespace for the retrace 0 mm