

GM5 63 IX A

12NC/Fx: F153496

GTIN (EAN) code: 8050147534960

DIMENSION	MEAS	UR
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	590	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	590	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	595	mn
MAX Height of the base cabinet niche, including all required space for installation or ventilation	595	mn
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	850	mn
MIN Width of the base cabinet niche, including all required space for installation or ventilation	850	mn
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	860	mn
MAX Width of the base cabinet niche, including all required space for installation or ventilation	860	mn
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mn
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mn
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mn
Space in front, which is required to install bottom trim	0	mn
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	
Minimum space or inbound ventilation (wall cabinet)	0	mn
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	
Minimum space or outbound ventilation (wall cabinet)	0	mn
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	50	mn
Minimum area for inbound ventilation cavity (tall cabinet)	292	cm
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Front	
Minimum space for outbound ventilation (tall cabinet)	5	mn
Minimum area for outbound ventilation cavity (tall cabinet)	45	cm
BASE CABINET (vent-shaft incoming)		•
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear	
Minimum space for inbound ventilation (base cabinet)	50	mn
Minimum area for inbound ventilation cavity (base cabinet)	292.5	
BASE CABINET (vent-shaft outgoing)	202.0	5.11
Indicates the position of the freespace for the outbound airflow (base cabinet)	Front	
Minimum space for outbound ventilation (base cabinet)	5	mn
Minimum area for outbound ventilation cavity (base cabinet)	45	cm
within a carlor outbound ventilation cavity (base cabinet)	40	CITI

DIMENSION M		EASURE	
APPLIANCE			
Height of the front	594	mm	
Width of the front	895	mm	
Depth of the front	21	mn	
Maximum depth all protruding elements, e.g. handles, controls	50	mn	
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	156	mm	
Projection of front in relation to housing of appliance	8	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	0	mm	
When product panel is missing, set to 0	115	mm	
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	1000	mm	
Height from bearing area of appliances and lower handle	421	mm	
Frontal handle thickness	30	mn	
Frontal handle width	583	mn	
MIN Height of the product body	581	mn	
MAX Height of the product body	580	mn	
Width of the product body	840	mn	
Depth of the product body	542	mn	
Full depth of product excluding protruding interface elements	563	mn	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No		
Appliance Flap door			
Projection of the opened flap in relation to bearing area	0	mn	
Maximum angle when flap door is opened totally	85	mm	
Appliance Side swing door			
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mn	
Lateral projection of opened front at the side where the hinge is fixed	0	mm	
Maximum angle when door is opened totally	0	mm	
Appliance other			
Depth from front end of the niche to the front end of the freespace of the retrace	55	mm	
Height from niche to bottom end of freespace for the retrace	581	mm	